


1. MATERIALS AND FINISHES
BODY - BRASS, NICKEL PLATING
CONTACT - BERYLLIUM COPPER, SILVER PLATING
INSULATOR - PTFE, NATURAL
2. ELECTRICAL:
 - A. IMPEDANCE: 50 OHM
 - B. FREQUENCY RANGE: DC 0-11 GHz
 - C. DIELECTRIC WITHSTANDING VOLTAGE: 2500 VRMS, MIN.
3. MECHANICAL:
 - A. DURABILITY: 500 CYCLES MIN.
 - B. TEMPERATURE RANGE: - 65°C to +165°C

REVISIONS

REV	DESCRIPTION	DATE	ECO	APPR
Y	REDRAWN TO UPDATE FORMAT	5-Jan-09'	47205	SH
AA	STAMP "AMPHENOL" WAS "74868"RD-DM11120601R3		48845	



ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE: 0.5 - 6mm 6 - 30mm 30 - 120mm ANGLES ±0.1mm ±0.2mm ±0.3mm ±1° NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.	MATERIAL	DRAWN	DATE	TITLE			Amphenol RF Danbury CT USA, Tainan Taiwan, Shenzhen China www.amphenolrf.com		
		R.MAO	12-Dec-11						
	REFERENCE	ENGINEER	DATE	N ADAPTER JACK TO JACK UG-29A/U			DRAWING NO. 82-65		
		N.CAO	07-May-03						
	FINISH	APPROVED	DATE	SCALE: 2.5/1 SHEET 2 OF 2			ITEM NO. 82-65		
S.HSIEH		12-Dec-11							
CAD FILE			DWG SIZE CODE ID REV						
F:\DWG\CNPD\82\65-AASZ	B	74868				AA			