

**Part Number :** 1202540075
**Product Description :** Contrinex Photoelectric Sensor, 4mm Diameter Smooth Housing, Diffuse, 20mm Operating Distance, PNP, Light-ON, 3-pin M8 Connector, 45mm Housing Length
**Series Number :** 120254
**Status :** Obsolete
**Product Category :** Inductive and Photoelectric Sensors
**Engineering Part Number :** LTR-D04MA-NMS-403

Obsolete

## Documents and Resources

### Specifications

1202540072-000.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21 |
| REACH SVHC | Not Reviewed per D(2025)7771-DC (04 Feb 2026) |
| EU RoHS | Compliant per EU 2015/863 |

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

UKCA - Declaration of Conformity

CE - Declaration of Conformity

---

## Part Details

### General

| | |
|---|---|
| Status | Obsolete |
| Category | Photoelectric Sensors |
| Series | 120254 |
| Description | Contrinex Photoelectric Sensor, 4mm Diameter Smooth Housing, Diffuse, 20mm Operating Distance, PNP, Light-ON, 3-pin M8 Connector, 45mm Housing Length |
| IP Rating | IP67 |
| Operating Principle | Diffuse |
| Product Name | Contrinex |
| Type | Photoelectric |
| UPC | 191130067718 |

### Electrical

| | |
|---|---|
| Output | Light-ON |
| Polarity | PNP |
| Switching Frequency | ≤ 250 Hz |

### Physical

| | |
|---|---|
| Connection | Connector (M8, 3-pin) |
| Length | 45mm |
| Material - Housing | Stainless Steel |
| Material - Window | Sapphire |
| Operating Distance | 20mm |
| Output | Light-ON |

Obsolete

| | |
|---|---|
| Sensor Housing Size | 4mm dia. (smooth) |
| Temperature Range - Operating | 0° to +55°C |



Obsolete