1210HC

High current surface mount brick fuse




Photo is representative

Product features

- High current rating from 50 A to 200 A for short circuit protection
- Fast-acting
- 12.4 mm x 10 mm x 6.8 mm surface mount package
- High breaking capacity for high power battery systems
- UL recognized according to UL248-1&13
- TUV conforms to IEC 60269-1&7
- Mositure sensitivity level (MSL): 1

Applications

Primary and secondary circuit protection:

- Data center
- Power distribution boards (PDB)
- Server and desktop power supplies
- Energy storage systems
- LED and general lighting
- Gaming console systems
- Storage system power
- Basic power supplies

Agency information

cURus Recognition file number: E56412

TUV: File number: R 50642360 0001 (< 125 A)
R 50642135 0001 (> 150 A)

Environmental compliance

Ordering part number

1210HC 150 - R TR

Family code
Ampere rating
RoHS compliant
Packaging code

Packaging code suffix

TR = tape and reel

Powering Business Worldwide

Electrical characteristics


	Opening time	
Current rating	**1.0 In**	**2.5 In**
50 A - 200 A	4 hours minimum	10 seconds maximum

Product specifications


Part number	Current rating (A)	Voltage rating (V)	Breaking capacity (A)	Typical cold resistance[1] (mΩ)	Resistance tolerance	Typical voltage drop[2] (mV)	Typical pre-melting[3] I^2t (A^2Sec)
1210HC50-RTR	50	125 Vdc 100 Vdc	6 kA @ 100 Vdc (TUV certified) 3 kA @ 125 Vdc (UL certified) 10 kA @ 80 Vdc (UL certified)	1.02	± 35%	79	925
1210HC60-RTR	60	125 Vdc 100 Vdc		0.81	± 35%	73	1575
1210HC70-RTR	70	125 Vdc 100 Vdc		0.65	± 35%	70	1750
1210HC80-RTR	80	125 Vdc 100 Vdc		0.58	± 35%	70	3920
1210HC100-RTR	100	125 Vdc 100 Vdc		0.47	± 35%	79	6410
1210HC125-RTR	125	125 Vdc 100 Vdc		0.35	± 35%	70	16450
1210HC150-RTR	150	100 Vdc 75 Vdc	3 kA @ 100 Vdc 10 kA @ 75 Vdc (TUV certified) 10 kA @ 80 Vdc (UL certified)	0.30	± 50%	73	19000
1210HC175-RTR	175	100 Vdc 75 Vdc		0.27	± 50%	74	25700
1210HC200-RTR	200	100 Vdc 75 Vdc		0.24	± 50%	78	40000

1. Cold resistance is measured at <10% rated current
2. Typical voltage drop is measured at rated current
3. Typical pre-melting I^2t is measured at 10 In

Dimensions - mm



Recommended layout - mm



A	3.0
B	10.0
C	8.0

*Above land pattern is recommended for reflow soldering;
Recommended stencil thickness: 0.15 mm
Recommend 5 mm^2 minimum trace for 70 A and below.
Recommend 7 mm^2 minimum trace for 80 A to 125 A.
Recommend 17 mm^2 minimum trace for 150 A and above.

Amp rating	L	W	T	L1	L2	W1	T1	T2
50 A - 200 A	12.4 ±0.5	10.0 ±0.2	6.8 +0.3/-0.1	1.6 ±0.2	11.8 ±0.2	6.3 ±0.2	6.5 ±0.2	2.3 ±0.5

Marking requirements

1210HC50-R	1210HC60-R	1210HC70-R	1210HC80-R	1210HC100-R
BUSS 1210HC-50 50 A 125 Vdc	BUSS 1210HC-60 60 A 125 Vdc	BUSS 1210HC-70 70 A 125 Vdc	BUSS 1210HC-80 80 A 125 Vdc	BUSS 1210HC-100 100 A 125 Vdc


1210HC125-R	1210HC150-R	1210HC175-R	1210HC200-R
BUSS 1210HC-125 125 A 125 Vdc	BUSS 1210HC-150 150 A 100 Vdc	BUSS 1210HC-175 175 A 100 Vdc	BUSS 1210HC-200 200 A 100 Vdc

General specifications

Operating temperature: -40 °C to +105 °C with proper correction factor applied
Temperature and humidity cycling: JASO D622, 10 cycles
Temperature cycling: -40 °C to +125 °C, 1000 cycles
Humidty bias: MIL-STD-202, method 103, 10% In, 85% +85 °C, 1000 hours
Resistance to solvents: MIL-STD-202, method 215
Vibration: MIL-STD-202, method 204, 5g 20 minutes, 12 cycles
Mechanical shock: MIL-STD-202, method 213, test condition C (100 g's peak for 6 milliseconds)
Board flex: AEC-Q200-005
Terminal strength (SMD): AEC-Q200-006
Resistance to solder heat: MIL-STD-202, method 210
Solderability: MIL-STD-202, method 208
Salty spray: MIL-STD-202 method 101 test condition B, (5% NaCL solution, 48 hours exposure)
High temperature operating life: +105 °C, 0.5 In, 1000 hours
Shelf life: 3 years @ +25 ±-5 °C, 50%RH maximum in the original packaging


Packaging information - mm

500 pieces per reel, 5 reels (2500 pieces) in the carton




Dimension	Millimeter
W ± 0.30	24.0
F	11.5
E1 ± 0.10	1.75
P0 ± 0.10	4.00
P1 ± 0.10	16.0
P2	2.0
D0 + 0.10/-0	1.50
D1 Minimum	1.50
A0 ± 0.10	10.5
B0 ± 0.10	13.0
B1 Maximum	15.8
K0 ± 0.10	7.30
T Maximum	0.60
T1 Maximum	0.10
T2 Maximum	8.00

Reel dimension - mm




Dimension	Millimeter
A	330
B	2.50
C	13.5
D	21.5
N	100
W1	24.8
W2	29.0


Temperature derating curve




Time vs. current curves



I²t vs. time curve



I²t vs. current curve



Reflow soldering characteristics




Table 1 - Standard SnPb solder (T_C)

Package thickness	Volume mm3 <350	Volume mm3 ≥350
<2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2 - Lead (Pb) free solder (T_C)

Package thickness	Volume mm³ <350	Volume mm³ 350 - 2000	Volume mm³ >2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 – 2.5 mm	260 °C	250 °C	245 °C
>2.5 mm	250 °C	245 °C	245 °C

Reference J-STD-020

Profile feature		Standard SnPb solder	Lead (Pb) free solder
Preheat and soak	• Temperature minimum (T_{smin})	100 °C	150 °C
	• Temperature maximum (T_{smax})	150 °C	200 °C
	• Time (T_{smin} to T_{smax}) (t_s)	60-120 seconds	60 to120 seconds
Ramp up rate T_L to T_p		3 °C/ second maximum	3 °C/ second maximum
Liquidous temperature (T_L) Time (t_L) maintained above T_L		183 °C 60 to 150 seconds	217 °C 60 to 150 seconds
Peak package body temperature (T_p)*		See Table 1	See Table 2
Time (t_p)* within 5 °C of the specified classification temperature (T_C)		20 seconds*	30 seconds*
Ramp-down rate (T_p to T_L)		6 °C/ second maximum	6 °C/ second maximum
Time 25 °C to peak temperature		6 minutes maximum	8 minutes maximum

* Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com/electronics

© 2026 Eaton
All Rights Reserved
Printed in USA
Publication No. ELX1447
Published February 2026

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.