PROT-M12 FS-M-CHAIN - Sealing cap

1430491

https://www.phoenixcontact.com/nl/products/1430491

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sealing cap, this item is expected to be lead-free from Q2 2026 in accordance with RoHS II without exception 6c (Pb < 0.1%), a lead-free alternative is possible on request in advance

Commercial data

Item number	1430491
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	ABQZAB
Product key	ABQZAB
GTIN	4046356325783
Weight per piece (including packing)	13,56 g
Weight per piece (excluding packing)	13,216 g
Customs tariff number	74198090
Country of origin	DE

Technical data

Notes

General	Use up to max. 48 V AC and 60 V DC

Product properties

Thread type	M12

Material specifications

Material	CuZn/Ni (Chain)
Seal material	NBR

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67
	IP69K
Ambient temperature (operation) (male connector/female connector)	-40 °C ... 85 °C

Classifications

ECLASS

ECLASS-13.0	27440208
ECLASS-15.0	27440208

ETIM

ETIM 10.0	EC002314

UNSPSC

UNSPSC 21.0	39121400

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	addbf47c-56c5-4617-9dcb-dde2af51a873

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT B.V.
Hengelder 56 6902 PA Zevenaar
Postbus 246 6900 AE Zevenaar
(0316) 59 17 20
sales@phoenixcontact.nl