




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.2 – .51 mm²**

Mating Tab Width: **2.8 mm [.11 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

	.042 in
Wire Insulation Support	With
Mating Retention Type	Locking Lance

Dimensions

Product Length	14 mm[.551 in]
Compatible Insulation Diameter Range	1 – 1.6 mm[.039 – .062 in]
Terminal Material Thickness	.25 mm[.01 in]
Wire Size	.2 – .51 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Packaging Features

Packaging Quantity	10000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1-1579007-4
EXTRACTION TOOL



TE Part # 150571-2
FF 110 REC 0.2-0.56MM2 TPBR



TE Part # 539744-2
DIE F2,8FF TAB


Also in the Series | FASTIN-FASTON 110




Automotive Housings(6)



Automotive Signal & Power Connector
Housings(6)



Automotive Terminals(5)



Crimp Terminal Housings(34)




Insertion & Extraction Tools(3)



Quick Disconnects(78)

Customers Also Bought



TE Part #154717-4
PL 250 REC TERMINAL 13-11 AWG
TPPB




TE Part #213624-1
34 UNASSM KIT,M SERIES



TE Part #444312-1
HSG 12 POSN, FUSE CONTACT



TE Part #444313-1
HSG. ASS'Y 9 POSN. COM.




TE Part #880398-2
FUSE CONTACT



TE Part #CAT-T4827-T273
TIMER, RECEPTACLE AND TAB

TE Part #774385-000
SRFR-2.9/1.7-8-RSU-1M



TE Part #444308-2
FRAME FUSE RELAY BOX



TE Part #880399-2
FUSE CONTACT

Documents

Product Drawings

FF 110 REC 0.2-0.5MM2 TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_160922-2_B_c-160922-2-b.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_160922-2_B_c-160922-2-b.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_160922-2_B_c-160922-2-b.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications



Application Specification

English