








Leiterplatten-Layout Vorschlag für SMT
PCB-Layout Proposal for SMT




Anforderungsstufe 1
Performance Level 1

Kontaktbereich vergoldet
Mating Area gold plating


Anschlussbereich verzinkt 4-6 µm
Terminal Area 4-6 µm tin plating

Koplanarität der Anschlüsse ≤ 0,1 mm
Coplanarity Area of Termination ≤ 0,1 mm


Verpackt im Gurt in Anlehnung an DIN IEC 60286-3
Tape on Reel Packaging according to DIN IEC 60286-3
Verpackungseinheit: 420 Stück
Packaging unit: 420 pcs



Abspulrichtung - Reel off Direction



Copyright by ERNI Production GmbH & Co. KG
Proprietary notice pursuant to ISO 16016 to be observed.

Proprietary notice pursuant to ISO 9001 to be observed.	Information:			Tolerances		 All Dimensions in mm		Scale		5:1						
	All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.			Subject to modification without prior notice. Drawing will not be updated.		Designation 0,8 DRC-B, F 8mm, 26 polig <i>0,8 DRC-B, F 8mm, 26 pin</i>										
b			23.06.2016						www.ERNI.com			294027			I	
Index			Date						Class			DRCB			A3	