5164713-5 ✔ ACTIVE

MINI-MATCH

TE Internal #: 5164713-5

PCB Mount Header, Vertical, Board-to-Board, 5 Position, 2.5 mm [.098 in] Centerline, Unshrouded, Tin (Sn), Through Hole - Solder, Power & Signal

View on TE.com >

Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Header**

Connector System: **Board-to-Board**

Number of Positions: **5**

Centerline (Pitch): **2.5 mm [.098 in]**

PCB Mount Orientation: **Vertical**

Features

Product Type Features

PCB Connector Type	PCB Mount Header
Connector System	Board-to-Board
Header Type	Unshrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Number of Columns	5
Number of Positions	5
PCB Mount Orientation	Vertical

Body Features

Primary Product Color	Green

Contact Features

Mating Tab Width	2.79 mm[.11 in]
Contact Layout	Inline
Contact Base Material	Phosphor Bronze
Mating Tab Thickness	.5 mm[.02 in]
Contact Mating Area Plating Material	Tin (Sn)

Contact Type	Tab
Contact Current Rating (Max)	7 A
Contact Mating Area Plating Material Thickness	3.048 µm[120 µin]

Termination Features

Rectangular Termination Post & Tail Width	.78 mm[.03 in]
Rectangular Termination Post & Tail Thickness	.5 mm[.02 in]
Termination Post & Tail Length	3.2 mm[.125 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Connector Mounting Type	Board Mount
Mating Alignment	Without
PCB Mount Alignment	Without
PCB Mount Retention	Without

Housing Features

Centerline (Pitch)	2.5 mm[.098 in]
Housing Material	PBT GF20

Dimensions

Connector Width	6.3 mm[.248 in]
Connector Height	5.9 mm[.232 in]
Connector Length	12.5 mm[.492 in]
PCB Thickness (Recommended)	1.6 mm[.06 in]

Usage Conditions

Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]

Operation/Application

Circuit Application	Power & Signal

Industry Standards

Compatible With Agency/Standards Products	UL
UL Rating	Recognized
Compatible With Approved Standards Products	UL
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	3500

Packaging Method	Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 240°C

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




TE Part # 5164711-5
05pos.MINI-MATCH FBTB, 2.5mm pitch


Customers Also Bought



TE Part #215877-1
8/8 PCB MOD.JACK SE



TE Part #9-966140-6
MESSERLEISTE 21P



TE Part #1217080-1
FASTON 205/250 PCB MOUNTED TPBR



TE Part #4-1879011-7
SMF2 18K 5%



TE Part #7-1879128-7
RN 0402 1K0 0.1% 10PPM 1K RL



TE Part #2-2176089-5
RP 1J 0.166W 19K6 0.1% 25PPM 1K RL



TE Part #2-2176231-3
3522 82R 1% 3W



TE Part #2213831-2
BASE ASSY, 80MM, VENTED, SEALED



TE Part #1-2328823-1
LUMAWISE S 80MM DIA DOME CLEAR LOW



TE Part #5520251-4
MJ,R/A,8P,PNL STOPS

Documents

Product Drawings

5P.MINI-MATCH ASSY

English

CAD Files

Customer View Model

ENG_CVM_5164713-5_A.3d_igs.zip

English

Customer View Model

ENG_CVM_5164713-5_A.3d_stp.zip

English

Customer View Model

ENG_CVM_5164713-5_A.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Product Specification

Mini Match Connection System

English

Product Specification

English

Instruction Sheets

Instruction Sheet (non U.S.)

German