



Product Navigation

[Home](#)
[About Us](#)
[Products](#)
[Investor Relations](#)
[News](#)
[Contact Us](#)
[Secure EAX](#)

Circuit Board Indicators

Panel Mount Indicators

Solid State Lighting

Traffic Signals

Vehicle Lighting

Rail

Obstruction Lighting

Hazardous Area Lighting

Heliport Lighting

Circuit Board Indicators - Through Hole Indicators

P/N# **5219309F**

5 mm Lens Single Color

Description	Discrete LED Lamp
Package Options	100 pieces per bag
Product Type	Through Hole Indicators
Sub Product Type	Discrete LED
Configuration	5 mm Lens
Lamp Type	Single Color
Lens Color	Water Clear
Viewing Angle	20 degrees
Test Current (mA)	20mA

Absolute Maximum Ratings (Ta = 25 °)

Forward Current Continuous	50 mA
Forward Current Pulse	100 mA
Reverse Voltage	4 V
Solder Temp	260Å° for 5 sec
Operating Temp	-30~+100° C
Storage Temp	-30~+100° C
Peak Wave Length	605


RoHS / pB Free
view PDF

Distributor Stock Check

Check stock with our distributors now.

5219309F

[check stock](#)

how to purchase

[sales contacts](#)
[stock check](#)
[search](#)
[Product Line Search](#)

Please select a Product Line to search.

Circuit Board Indicators

[find](#)

Operating Characteristics

LED Position	
Color	Amber
Lamp Type	Single Color
LED Type	GaAsP/GaP
Intensity Min (mcd)	60
Intensity Typ (mcd)	90.0
Intensity Max (mcd)	
Fwd Voltage Min	
Fwd Voltage Typ	2.2
Fwd Voltage Max	2.5
Dom Wavelength Min (nm)	
Dom Wavelength Typ (nm)	
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	125
Backlighting	
Pitch Between Vertical	
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	

quick links

Dialight Corporate Video

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

Application Notes
FAQs

Dialight Ltd (UK)
Dialight Garufo
Dialight BLP
LumiDrives