

Connectors for Copper Conductor

One Hole Lugs - 90° Long Barrel 600V to 35KV

Material: High Conductivity Wrought Copper

Finish: Electro Tin Plate



Peep holes
available.
Add suffix -P
or suffix -PH



COMPRESSION

Cat. No.	Wire Size		Bolt Size	Dimensions (in.)					Die Code	Die Color
	Code	Flex		B	C	D	E	F		
54929BEUB 54930BEUB	#8 AWG	37/24 = 14.9 kcmil	#10 1/4	.65 .65	.42 .42	.08 .08	.26 .26	1/4 1/4	21	RED RED
54904BEUB 54905BEUB	#6 AWG	61/24 = 24.6 kcmil	#10 1/4	.65 .65	.44 .44	.08 .08	.30 .30	1/4 1/4	24	BLUE BLUE
54908BEUB 54906BEUB	#4 AWG	91/24 = 36.7 kcmil	#10 1/4	.65 .65	.52 .52	.10 .10	.37 .37	1/4 1/4	29	GREY GREY
54933BEUB 54942BEUB	#2-3 AWG	125/24 = 50.4 kcmil	#10 5/16	.65 .88	.59 .59	.11 .11	.41 .41	1/4 3/8	33	BROWN BROWN
54945BEUB 54947BEUB	#1 AWG	150/24 = 60.5 kcmil	#10 5/16	.65 .88	.68 .68	.11 .11	.47 .47	1/4 3/8	37	GREEN GREEN
54946BEUB 54949BEUB 54909BEUB 54950BEUB	1/0 AWG	225/24 = 90.8 kcmil	#10 5/16 3/8 1/2	.65 .88 .93 1.25	.75 .75 .75 .75	.13 .13 .13 .13	.52 .52 .52 .52	1/4 3/8 3/8 1/2	42	PINK PINK PINK PINK
54910BEUB 54951BEUB	2/0 AWG	275/24 = 111 kcmil	3/8 1/2	.93 1.25	.83 .83	.13 .13	.57 .57	3/8 1/2	45	BLACK BLACK
54965BEUB	3/0 AWG	325/24 = 131 kcmil	1/2	1.25	.92	.13	.63	1/2	50	ORANGE
54970BEUB04 54970BEUB06 54970BE	4/0 AWG	450/24 = 182 kcmil 3/0 Weld	1/4 3/8 1/2	1.00 1.13 1.25	1.03 1.03 1.03	.14 .14 .14	.70 .70 .70	1/4 3/8 1/2	54	PURPLE PURPLE PURPLE
54913BEUB	250 kcmil	550/24 = 222 kcmil, 4/0 Weld	1/2	1.25	1.13	.14	.77	1/2	62	YELLOW
54914BEUB	300 kcmil		1/2	1.25	1.25	.15	.85	1/2	66	WHITE
54915BEUB	350 kcmil	650/24 = 262 kcmil	1/2	1.25	1.36	.18	.93	1/2	71	RED
54916BEUB 54917BEUB	400 kcmil	775/24 = 313 kcmil	1/2 5/8	1.25 1.58	1.41 1.41	.17 .17	.96 .96	1/2 5/8	76	BLUE BLUE
54918BEUB 54919BEUB	500 kcmil	925/24 = 373 kcmil	1/2 5/8	1.25 1.58	1.61 1.61	.22 .22	1.10 1.10	1/2 5/8	87	BROWN BROWN
54921BEUB 54920BEUB	600 kcmil	1100/24 = 444 kcmil	1/2 5/8	1.25 1.58	1.75 1.75	.24 .24	1.20 1.20	1/2 5/8	94	GREEN GREEN
54922BEUB 54923BEUB	750 kcmil	1325/24 = 535 kcmil	1/2 5/8	1.25 1.58	1.94 1.94	.27 .27	1.33 1.33	1/2 5/8	106	BLACK BLACK
54984BEUB		1600/24 = 646 kcmil	5/8	1.58	1.94	.27	1.33	5/8	106	BLACK
58926BEUB	900 kcmil	1925/24 = 777 kcmil	5/8	1.58	2.17	.31	1.50	5/8	115	YELLOW
54928BEUB 54928BEUB12	1000 kcmil		5/8 7/8	1.58 1.83	2.27 2.37	.30 .30	1.55 1.55	5/8 7/8	125	N/A N/A

Tooling: Pg. 79-100

Die Selector Chart: Pg. 105-109

