Circuit Board Indicators
Panel Mount Indicators
Solid State Lighting
Traffic Signals
Vehicle Lighting
Rail
Obstruction Lighting
Hazardous Area Lighting
Heliport Lighting

how to purchase
sales contacts
stock check

search
Product Line Search
Please select a Product Line to search.
Circuit Board Indicators
find

Part # / Text Search
Part No.:
Text Search:
search

quick links
Dialight Corporate Video

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. View PDF File

Application Notes
FAQs

Dialight Ltd (UK)
Dialight Garufo
Dialight BLP
LumiDrives

Circuit Board Indicators - Through Hole Indicators

P/N# **5680121231F**

Rectangle Lens

Description	2X4 Quad-Level CBI R-G-Y-R
Package Options	5 Pieces Per Bag
Product Type	Through Hole Indicators
Sub Product Type	with Quad Level Housing
Configuration	Rectangle Lens
Viewing	Right Angle
Viewing Angle	104
Test Current (mA)	10mA

Absolute Maximum Ratings (Ta = 25 °)

Solder Temp	**260Â° for 5 sec**
Operating Temp	**-55 to +100° C**
Storage Temp	**-55 to +100° C**

RoHS /pB Free
view PDF

Distributor Stock Check

Check stock with our distributors now.

5680121231F

check stock

Operating Characteristics

LED Position	Found in position(s): 1,4	Found in position(s): 2	Found in position(s): 3
Color	Red	Green	Yellow
Lamp Type	Single Color	Single Color	Single Color
LED Type	High Efficiency	High Efficiency	High Efficiency
Intensity Min (mcd)	1.1	0.0	0.0
Intensity Typ (mcd)	3.7		
Intensity Max (mcd)			
Fwd Voltage Min			
Fwd Voltage Typ			
Fwd Voltage Max			
Dom Wavelength Min (nm)	588	588	588
Dom Wavelength Typ (nm)			
Dom Wavelength Max (nm)			
Power Dissipation Max (mW)	100	100	60
Backlighting			
Pitch Between Vertical			
Pitch Between Horizontal			
Lum Intensity Min			
Lum Intensity Typ			
Lum Intensity Max			

Dialight

Copyright 2006 Dialight. All rights reserved | Privacy Policy