5787394-2 ✔ ACTIVE


AMPLIMITE | AMPLIMITE 0.50 Series

TE Internal #: 5787394-2

26 Position D-Shaped Connector, Receptacle, Cable-to-Board, Board Mount, 1.27 mm [.05 in] Centerline, Printed Circuit Board, AMPLIMITE 0.50 Series

View on TE.com >

Connectors > D-Shaped Connectors > D-Sub Receptacle Assembly: Right Angle, 1.27mm



Number of Positions: **26**

Connector & Housing Type: **Receptacle**

Connector System: **Cable-to-Board**

Connector Mounting Type: **Board Mount**

Centerline (Pitch): **1.27 mm [.05 in]**

All D-Sub Receptacle Assembly: Right Angle, 1.27mm (73)

Features

Product Type Features

Shell Material Configuration	Full Metal Shell
Connector & Housing Type	Receptacle
Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	26
Number of Rows	2
PCB Mount Orientation	Right Angle

Body Features

Shell Plating Finish	Bright
Shell Plating Material	Nickel over Copper
Primary Product Color	Black
Connector Profile	Standard

Contact Features

	30 µin
Contact Underplating Material	Palladium Nickel
Contact Mating Area Plating Material	Gold (Au)

Contact Base Material	Phosphor Bronze
PCB Contact Termination Area Plating Material	Tin over Nickel
Contact Current Rating (Max)	1 A
Contact Options	Installed

Termination Features

Rectangular Termination Post & Tail Width	.41 mm[.016 in]
Rectangular Termination Post & Tail Thickness	.3 mm[.011 in]
Termination Method to PCB	Through Hole - Solder
Termination Post & Tail Length	2.54 mm[.1 in]

Mechanical Attachment

	.109 in
Mounting Feature Plating Material	Nickel over Copper
Mounting Feature Material	Zinc
Mating Alignment	Without
PCB Mount Alignment	Without
Connector Mounting Type	Board Mount
PCB Mount Retention	Without
Mating Retention	With
Mating Retention Type	Latch

Housing Features

Housing Material	Thermoplastic
Shell Material	Carbon Steel
Centerline (Pitch)	1.27 mm[.05 in]

Dimensions

PCB Thickness (Recommended)	1.57 mm[.062 in]
Row-to-Row Spacing	2.54 mm[.1 in]

Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]

Operation/Application

Shielded	Yes
Circuit Application	Signal

Industry Standards

UL Flammability Rating	UL 94V-0
Compatible With Approved Standards Products	UL E28476

Packaging Features

Packaging Quantity	14
Packaging Method	Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 5750913-2
26 50SR CABLE CONN KIT


Also in the Series | AMPLIMITE 0.50 Series

Connector Hardware(6)

D-Shaped Connectors(234)

D-Sub Backshells & Clamps(20)

IDC D-Sub Connectors(63)



Panel Mount D-Sub Connectors(27)

Customers Also Bought

TE Part #203346-E
MJIM IMV 1X1 S 810 * X R THRU * L9A M5B0

TE Part #5-146131-6
14 MODII HDR DRST SFMNT B/A LF

TE Part #2-382811-1
SHUNT, ECON, PHBRSN, BLACK

TE Part #1-796409-1
CPC PSTD RCPT,23-37,R/A LF



TE Part #1734035-4
MINI USB, TYPE B, R/A, SMT, MYLAR



TE Part #1981568-1
MICRO USB, TYPE B,



TE Part #2176487-1
BMC 0805 300R 25% A Med C



TE Part #5787082-2
26 50SR R/A RCPT ASSY,RDSN L/F

TE Part #84987-3
FALCON,PRINTER CONN ASSY,81P

TE Part #1825027-3
FSMRA1JHA04=R/A,TACT PB SW,260

Documents

Product Drawings

26 50SR R/A RCPT ASSY, LD FREE

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5787394-2_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5787394-2_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5787394-2_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Application Specification

English

Agency Approvals

UL

English