




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**

Wire Size: **.82 – 2.08 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Tab
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Hole

Dimensions

Product Length	21.33 mm[.84 in]
Compatible Insulation Diameter Range	.8 – 2 mm[.031 – .078 in]
Terminal Material Thickness	.85 mm[.033 in]
Wire Size	.82 – 2.08 mm ²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	UL
---	----

Packaging Features

Packaging Quantity	500
Packaging Method	Loose Piece/Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 90165-1
DAHT 250 FASTON REC 18-14 ASSY



TE Part # 575046-1
DAHT 250 FASTON 22-14 ASSY



TE Part # 63771-1
187 FASTON TAB NPST



TE Part # 626417-2
250 FASTON REC 22-18 AWG TPBR



TE Part # 42559-1
250 FASTON TAB NPST



TE Part # 61960-1
187 FASTON TAB NPST



TE Part # 63953-1
187 FASTON TAB



TE Part # 63402-3
312 FASTON TAB BR




TE Part # 63402-2
312 FASTON TAB NPST

Also in the Series | FASTON 250



[Compression Connectors\(4\)](#)




[Crimp Terminal Housings\(115\)](#)



[Insertion & Extraction Tools\(6\)](#)



[Insulation Boots & Sleeves\(16\)](#)



[Magnet Wire Terminals\(1\)](#)



[PCB Terminals\(133\)](#)




[Quick Disconnects\(417\)](#)



[Splices\(4\)](#)

Customers Also Bought




TE Part #42241-2
[FF 250 TAB 18-14 AWG .032 TPBR](#)



TE Part #151680
[2 WAY MATE-N-LOK SOC HSG NAT.](#)




TE Part #170263-1
[EIS CONTACT](#)



TE Part #173682-1
[040 MLC TAB CONTACT](#)



TE Part #6-176143-6
[187 CAP HSG ASSY 2P LIGHT GRAY](#)



TE Part #353842-1
[FPC SENSOR CONT.](#)



TE Part #927824-2
[SPT REC 6.3 Contact SRC Sn](#)



TE Part #3-967325-3
[2,5MM BU-GEH 2P,GN](#)



TE Part #2204534-1
[ELCON MINI 3P CABLE CONN,PULL-TAB](#)



TE Part #2-6609037-6
[12EP1=F8217](#)

Documents



Product Drawings

250 FASTON TAB 18-14 AWG TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_60006-2_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_60006-2_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_60006-2_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Agency Approvals

Agency Approval Document

English