
**Part Number :** 768671012
**Product Description :** iPass+ HD Internal Cable and Connector Assembly, 1x2 , 0.76µm, Lead-Free
**Series Number :** 76867
**Status :** Active
**Product Category :** High-Speed I/O Connectors



## Documents & Resources

### Drawings

768671012_sd.pdf

PK-76867-001-001.pdf

### 3D Models and Design Files

STEP AP242

SOLIDWORKS

Creo

EE-76866-1004-001.pdf

SP-76866-001-001.zip

SP-76866-100-001.zip

SP-76866-1004-001.zip

### Specifications

AS-76867-001-001.pdf

AS-76867-002-001.pdf

PS-76867-001-001.pdf

TS-76866-1004-001.pdf

TS-76867-001-001.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | per SJ/T 11365-2006 |
| EU ELV | Not Relevant |

| | |
|---|---|
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2025)4165-DC (25 June 2025) |
| EU RoHS | Compliant per EU 2015/863 |

Compliance Statements
- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest
- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

## Part Details

### General

| | |
|---|---|
| Status | Active |
| Category | High-Speed I/O Connectors |
| Series | 76867 |
| Description | iPass+ HD Internal Cable and Connector Assembly, 1x2 , 0.76µm, Lead-Free |
| Application | Wire-to-Board |
| Component Type | Internal Receptacle |
| Product Name | iPass+ |
| Type | Pluggable |
| UPC | 887191049229 |

### Agency

| | |
|---|---|
| CSA | LR19980 |
| UL | E107635 |

## Electrical

| | |
|---|---|
| Current - Maximum per Contact | 1.0A |
| Voltage - Maximum | 30V AC (RMS)/DC |

## Physical

| | |
|---|---|
| Circuits (Loaded) | 72 |
| Circuits (maximum) | 72 |
| Color - Resin | Black |
| Durability (mating cycles max) | 250 |
| Flammability | 94V-0 |
| Lock to Mating Part | Yes |
| Material - Metal | High Performance Alloy (HPA) |
| Material - Plating Mating | Gold |
| Material - Plating Termination | Tin |
| Material - Resin | High Temperature Thermoplastic |
| Net Weight | 8.145/g |
| Number of Rows | 1 |
| Orientation | Right Angle |
| Packaging Type | Tray |
| Panel Mount | No |
| PCB Locator | Yes |
| PCB Retention | Yes |
| PCB Thickness - Recommended | 1.37mm |
| Pitch - Mating Interface | 0.75mm |
| Pitch - Termination Interface | 0.75mm |
| Plating min - Mating | 0.762µm, 1.524µm |
| Polarized to Mating Part | Yes |
| Polarized to PCB | Yes |
| Ports | 2 |
| Temperature Range - Operating | -40° to +80°C |
| Termination Interface Style | Through Hole - Compliant Pin |

## Solder Process Data

| | |
|---|---|
| Lead-Free Process Capability | N/A |

## Mates With / Use With

### Mates with Part(s)

| Description | Part Number |
|---|---|
| Internal iPass+ HD-to-iPass+ HD, 4X Short Body Cable Assemblies | 100171 |
| Internal iPass+ HD-to-iPass+ HD, 8X Short Body Cable Assemblies | 100172 |
| Internal iPass+ HD-to-iPass+ HD, 4X Short Body Cable Assemblies | 100189 |
| Internal iPass+ HD-to-iPass+ HD, 8X Short Body Cable Assemblies | 100190 |
| Internal iPass+ HD-to-iPass+ HD, 4X Short Body Cable Assemblies | 100219 |
| Internal iPass+ HD-to-iPass+ HD, 8X Short Body Cable Assemblies | 100220 |
| Internal iPass+ HD-to-iPass+ HD, 4X Short Body Cable Assemblies | 100221 |
| Internal iPass+ HD-to-iPass+ HD, 4X Short Body Cable Assemblies | 100222 |
| Internal iPass+ HD-to-iPass+ HD, 4X Short Body Cable Assemblies | 100223 |
| Internal iPass+ HD-to-iPass+ HD, 8X Short Body Cable Assemblies | 100224 |
| Internal iPass+ HD-to-iPass+ HD, 8X Short Body Cable Assemblies | 100225 |
| Internal iPass+ HD-to-iPass+ HD, 8X Short Body Cable Assemblies | 100226 |

## Application Tooling