



Color:  light gray

Electrical data

Ratings per IEC/EN		Ratings per IEC/EN 2	
Nominal voltage (III/3)	600 V	Rated voltage (III/3) 2	1000 V

General

Voltage type 1	AC
Voltage type 2	DC

Connection data

Number of levels	1	Connection 1	
		Connection technology	Screw connection
		Actuation type	Operating tool
		Connectable conductor materials	Copper
		Solid conductor	6 ... 35 mm² / 10 ... 2 AWG
		Stranded conductor	6 ... 35 mm² / 10 ... 2 AWG
		Fine-stranded conductor	4 ... 25 mm² / 12 ... 4 AWG
		Fine-stranded conductor; with insulated ferrule	4 ... 25 mm² / 12 ... 4 AWG
		Strip length	14 mm / 0.55 inches

Mechanical Data

Torque	4 Nm
--------	------



Material Data	
Note (material data)	Information on material specifications can be found here
Color	light gray
Fire load	0 MJ
Weight	20 g

Commercial data	
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	16 (4) pcs
Packaging type	Box
Country of origin	DE
GTIN	4050821838654
Customs tariff number	85369010000