
PRODUCT NO.
92140

PRODUCT NO. 92140-XXXX	STAND OFF DIM "M" (mm)	SOLDER TAIL	DIM "P" (mm)	DIM "Q" (mm)	FOR LOWER DECK OR UPPER DECK	① HOLD DOWN	② LOCATOR FOR SOLDER TAIL ALIGNMENT	SHEET NO.	MOUNTING STYLE TO PCB
000	0	R/A	2.8	-#-	LOWER	NONE	NONE	NO.2	TOP MOUNT 92140-0XXX
000M	0	R/A	2.8	-#-	LOWER	NONE	NONE		
000LF	0	R/A	2.8	-#-	LOWER	NONE	NONE		
000MLF	0	R/A	2.8	-#-	LOWER	NONE	NONE		
000H	0	R/A	2.8	-#-	LOWER	YES	NONE		
000HLF	0	R/A	2.8	-#-	LOWER	YES	NONE		
001	0	SMT STG.	-#-	-#-	LOWER	NONE	NONE		
001LF	0	SMT STG.	-#-	-#-	LOWER	NONE	NONE		
001H	0	SMT STG.	-#-	-#-	LOWER	YES	NONE		
001HLF	0	SMT STG.	-#-	-#-	LOWER	YES	NONE		
002	0	SMT I.L.	-#-	-#-	LOWER	NONE	NONE		
002LF	0	SMT I.L.	-#-	-#-	LOWER	NONE	NONE		
002H	0	SMT I.L.	-#-	-#-	LOWER	YES	NONE		
002HLF	0	SMT I.L.	-#-	-#-	LOWER	YES	NONE		
010	4	R/A	2.8	-#-	LOWER	NONE	YES	NO.3	
010LF	4	R/A	2.8	-#-	LOWER	NONE	YES		
010H	4	R/A	2.8	-#-	LOWER	YES	YES		
010HLF	4	R/A	2.8	-#-	LOWER	YES	YES		
020	5	R/A	2.8	-#-	LOWER	NONE	YES		
020LF	5	R/A	2.8	-#-	LOWER	NONE	YES		
020MLF	5	R/A	2.8	-#-	LOWER	NONE	YES		
021MLF	5	R/A	2.8	-#-	LOWER	NONE	YES		
020H	5	R/A	2.8	-#-	LOWER	YES	YES		
020HLF	5	R/A	2.8	-#-	LOWER	YES	YES		
026HLF	5	R/A	2.8	-#-	LOWER	YES	YES		
040	2	R/A	2.5	-#-	LOWER	NONE	NONE		
040LF	2	R/A	2.5	-#-	LOWER	NONE	NONE		
040HLF	2	R/A	2.5	-#-	LOWER	YES	NONE		
050	3	R/A	2.8	-#-	LOWER	NONE	YES		
050LF	3	R/A	2.8	-#-	LOWER	NONE	YES		
050H	3	R/A	2.8	-#-	LOWER	YES	YES		
050HLF	3	R/A	2.8	-#-	LOWER	YES	YES		
005	FOR 0	R/A	2.8	8.6	UPPER	NONE	YES	NO.4	
005LF	FOR 0	R/A	2.8	8.6	UPPER	NONE	YES		
045	FOR 2	R/A	2.5	10.3	UPPER	NONE	YES		
045LF	FOR 2	R/A	2.5	10.3	UPPER	NONE	YES		
500	0	R/A	2.8	-#-	LOWER	NONE	NONE	NO.5	BOTTOM MOUNT 92140-5XXX
500LF	0	R/A	2.8	-#-	LOWER	NONE	NONE		
500H	0	R/A	2.8	-#-	LOWER	YES	NONE		
500HLF	0	R/A	2.8	-#-	LOWER	YES	NONE		
501	0	SMT STG.	-#-	-#-	LOWER	NONE	NONE		
501LF	0	SMT STG.	-#-	-#-	LOWER	NONE	NONE		
501H	0	SMT STG.	-#-	-#-	LOWER	YES	NONE		
501HLF	0	SMT STG.	-#-	-#-	LOWER	YES	NONE		
502	0	SMT I.L.	-#-	-#-	LOWER	NONE	NONE		
502LF	0	SMT I.L.	-#-	-#-	LOWER	NONE	NONE		
502H	0	SMT I.L.	-#-	-#-	LOWER	YES	NONE		
502HLF	0	SMT I.L.	-#-	-#-	LOWER	YES	NONE		
503	0	SMT I.L.	-#-	-#-	LOWER	NONE	NONE		
503LF	0	SMT I.L.	-#-	-#-	LOWER	NONE	NONE		
510	4	R/A	2.8	-#-	LOWER	NONE	YES	NO.6	
510LF	4	R/A	2.8	-#-	LOWER	NONE	YES		
510HLF	4	R/A	2.8	-#-	LOWER	YES	YES		
520	5	R/A	2.8	-#-	LOWER	NONE	YES		
520LF	5	R/A	2.8	-#-	LOWER	NONE	YES		
520H	5	R/A	2.8	-#-	LOWER	YES	YES		
520HLF	5	R/A	2.8	-#-	LOWER	YES	YES		
530	2	R/A	1.48	-#-	LOWER	NONE	NONE		
530LF	2	R/A	1.48	-#-	LOWER	NONE	NONE		
540	2	R/A	2.5	-#-	LOWER	NONE	NONE		
540LF	2	R/A	2.5	-#-	LOWER	NONE	NONE		
505	FOR 0	R/A	2.8	8.6	UPPER	NONE	YES	NO.7	
505LF	FOR 0	R/A	2.8	8.6	UPPER	NONE	YES		
535	FOR 2	R/A	1.48	9.28	UPPER	NONE	YES		
535LF	FOR 2	R/A	1.48	9.28	UPPER	NONE	YES		
545	FOR 2	R/A	2.5	10.3	UPPER	NONE	YES		
545LF	FOR 2	R/A	2.5	10.3	UPPER	NONE	YES		



92140-X X X X X X

- OPTIONAL LEED FREE: NONE : N O; LF : YES
- OPTIONAL HOLD DOWN: NONE : N O; H : YES (SEE FIGURE OF -xxxH)
- LOW COST VERSION: NONE : N O; M : YES (DETAIL AS COMPONENT)
- SOLDER TAIL: 0 : R/A (FOR LOWER & SINGLE); 1 : SMT STAGGERED; 2 : SMT IN LINE; 3 : SMT IN LINE (FOR UPPER ONLY); 5 : R/A; 6 : R/A (FOR LOWER & SINGLE, HOLD DOWN WITH HANGNAIL)
- STAND OFF: 0 : 0mm; 1 : 4mm; 2 : 5mm; 3 : 2mm (SPECIAL TAIL LENGTH); 4 : 2mm; 5 : 3mm
- MOUNTING STYLE: 0 : TOP MOUNTING; 5 : BOTTOM MOUNTING



92140-xxxH
(OPTIONAL HOLD DOWN)

NOTE
1. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
2. PRODUCT SPEC: 110-263

ltr	ecn no	dr	date
AL	ELX-N-011428	ZK	04/23/12
AM	ELX-N-16398	JH	11/29/13
AH	N08-0219	MZ	11/14/08
AJ	N09-0045	SH	05/26/09
AK	ELX-N-007949	ZK	11/01/11

sheet index | revision AM | sheet 1-7

mat'l. code

surface ISO 1302

tolerance ISO 406 ISO 1101

tolerances unless otherwise specified

angles ±2° | linear 0.X±0.3, 0.XX±0.13, 0.XXX±0.051

projection

MM

scale

dr	Mike Zhou	11/21/06
engr	Mike Zhou	11/21/06
chr	David Qin	11/21/06
appd	Jack Wang	11/21/06

product family PCMCIA

title 68 POS EJECTOR HEADER ASSY FOR 5.0V APPLICATION

dwg no 92140 | sheet 1 of 7 | size A4

type CUSTOMER Drawing

This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.


FCI CONFIDENTIAL


FCIconnect.com

form: A3


PDS: Rev :AM STATUS:Released Printed: Dec 06, 2013

PRODUCT NO.
92140-000M
92140-000MLF
92140-000H
92140-000HLF
92140-001
92140-001LF
92140-001H
92140-001HLF
92140-002
92140-002LF
92140-002H
92140-002HLF






R/A (92140-000X)



SMT STAGGERED (92140-001X)



SMT IN LINE (92140-002X)

NOTES
① TRUE POSITION IS A FREE GRID TO PIN PATTERN ITSELF.
2. SEE TA-946 FOR PCB LAYOUT.
③ MATERIAL HOUSING : HIGH TEMPERATURE THERMOPLASTIC UL94V-0 BLACK
PIN : COPPER ALLOY.
HOLD-DOWN : BRASS
④ FINISH PIN
UNDER PLATING : 0.5um MIN. Ni.
CONTACT AREA : 0.076 μm MIN. GOLD
NOTE:SPECIAL VERSION:ONLY 0.25uM Au
SOLDER AREA : 2.5um MIN. Sn-Pb.
OR 2.5um MIN. PURE Sn.(FOR -XXXLF)
HOLD-DOWN : 2.5um MIN. PURE Sn.
5. RECOMMENDED PCB HOLE (OPTIONAL HOLD-DOWN) : 2.3±0.1
6. SEQUENCE PIN ASSIGNMENT


	DIM "L"		
	4.25±0.1	3.5±0.1	5.0±0.1
PIN No.	OTHERS	36.67	1.17,34 35,51,68

7. GENERAL TOLERANCE : ±0.3
8. SEE SHEET 1 REGARDING COMPONENTS.


mat'l. code				surface	tolerance	projection	product family	PCMCIA
				ISO 1302	ISO 406 ISO 1101			
ltr	ecn no	dr	date	tolerances unless otherwise specified			title	68 POS EJECTOR HEADER ASSY FOR 5.0V APPLICATION
AM				angles	linear 0.X±0.3	MM		
				±2°	0.XX±0.13			
					0.XXX±0.051	scale		
				dr Mike Zhou	11/21/06		dwg no 92140	sheet 2 of 7 size A4
				engr Mike Zhou	11/21/06			
				chr David Qin	11/21/06			
				appd Jack Wang	11/21/06		type CUSTOMER	Drawing
sheet index	revision sheet							


FCI CONFIDENTIAL
FCIconnect.com
This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.

PRODUCT NO.	PRODUCT NO.
92140-010	92140-010LF
92140-010H	92140-010HLF
92140-020	92140-020LF
92140-020H	92140-020HLF
92140-040	92140-040LF
92140-050	92140-050LF
92140-050H	92140-050HLF
92140-020MLF	92140-040HLF
92140-021MLF	
92140-026HLF	





ONLY FOR 92140-020MCLF/ 021MCLF (WITHOUT RIB)






SECTION "Z"-"Z" (5/1)





DETAIL "Y" (5/1)



POINTED PIN TIP

DETAIL "X" (20/1)
TYP(68)

NOTES
① TRUE POSITION IS A FREE GRID TO PIN PATTERN ITSELF.
2. SEE TA-946 FOR PCB LAYOUT.
③ MATERIAL
HOUSING : HIGH TEMPERATURE THERMOPLASTIC UL94V-0 BLACK
PIN : COPPER ALLOY
HOLD-DOWN : BRASS
④ FINISH
PIN
UNDER PLATING : 0.5μm MIN. Ni.
CONTACT AREA 1 : 0.076 μm MIN. GOLD
CONTACT AREA 2 : 0.076 μm MIN. GOLD (FOR -XXXMLF).
SOLDER AREA : 2.5μm MIN. Sn-Pb.
OR 2.5μm MIN. PURE Sn.(FOR -XXXLF&XXXMLF)
HOLD-DOWN : 2.5μm MIN. PURE Sn.
5. RECOMMENDED PCB HOLE (OPTIONAL HOLD-DOWN) : 2.3±0.1
6. SEQUENCE PIN ASSIGNMENT

	DIM "L"		
PIN No.	4.25±0.1	3.5±0.1	5.0±0.1
	OTHERS	36.67	1,17,34,35,51,68

7. GENERAL TOLERANCE : ±0.3
8. SEE SHEET 1 REGARDING COMPONENTS.
9. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

ltr	ecn no	dr	date
AM			


dr	Mike Zhou	11/21/06
engr	Mike Zhou	11/21/06
chr	David Qin	11/21/06
appd	Jack Wang	11/21/06


mat'l. code
surface ISO 1302
tolerance ISO 406 ISO 1101
projection
tolerances unless otherwise specified
angles ±2°
linear 0.X±0.3, 0.XX±0.13, 0.XXX±0.051
MM
scale
sheet index
revision sheet


product family: PCMCIA
title: 68 POS EJECTOR HEADER ASSY FOR 5.0V APPLICATION
dwg no 92140
sheet 3 of 7
size A4
type CUSTOMER Drawing

FCI CONFIDENTIAL
FCIconnect.com
This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.


PRODUCT NO.
92140-005
92140-005LF
92140-045
92140-045LF









SECTION "Z"-"Z" (5/1)





DETAIL "Y" (5/1)



DETAIL "X" (20/1)
TYP(68)

NOTES

① TRUE POSITION IS A FREE GRID TO PIN PATTERN ITSELF.
2. SEE TA-946 FOR PCB LAYOUT.
③ MATERIAL
HOUSING : HIGH TEMPERATURE THERMOPLASTIC UL94V-0 BLACK
PIN : COPPER ALLOY
HOLD-DOWN : BRASS
④ FINISH
PIN
UNDER PLATING : 0.5um MIN. Ni.
CONTACT AREA : 0.076 µm MIN. GOLD
SOLDER AREA : 2.5um MIN. Sn-Pb.
OR 2.5um MIN. PURE Sn.(FOR -XXXLF)
HOLD-DOWN : 2.5um MIN. PURE Sn.
5. RECOMMENDED PCB HOLE (OPTIONAL HOLD-DOWN) : 2.3±0.1
6. SEQUENCE PIN ASSIGNMENT


	DIM "L"		
	4.25±0.1	3.5±0.1	5.0±0.1
PIN No.	OTHERS	36.67	117.34 35.51.68


7. GENERAL TOLERANCE : ±0.3
8. SEE SHEET 1 REGARDING COMPONENTS.
9. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008


mat'l. code				surface		tolerance	projection	product family	PCMCIA
				ISO 1302		ISO 406 ISO 1101			
ltr	ecn no	dr	date	tolerances unless otherwise specified				title	68 POS EJECTOR HEADER ASSY FOR 5.0V APPLICATION
AM				angles	linear	0.X±0.3	MM		
				±2°		0.XX±0.13			
						0.XXX±0.051	scale		
				dr	Mike Zhou	11/21/06		dwg no 92140	sheet 4 of 7 size A4
				engr	Mike Zhou	11/21/06			
				chr	David Qin	11/21/06			
				appd	Jack Wang	11/21/06		type CUSTOMER	Drawing
sheet index	revision sheet								

FCI CONFIDENTIAL
FCIconnect.com
This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.


PRODUCT NO.
92140-500
92140-500LF
92140-500H
92140-500HLF
92140-501
92140-501LF
92140-501H
92140-501HLF
92140-502
92140-502LF
92140-502H
92140-502HLF
92140-503
92140-503LF








R/A (92140-500X)



SMT STAGGERED (92140-501X)



SMT IN LINE (92140-502X)

NOTES
① TRUE POSITION IS A FREE GRID TO PIN PATTERN ITSELF.
2. SEE TA-946 FOR PCB LAYOUT.
③ MATERIAL
HOUSING : HIGH TEMPERATURE THERMOPLASTIC UL94V-0 BLACK
PIN : PHOSPHOR BRONZE.
HOLD-DOWN : BRASS
④ FINISH
PIN
UNDER PLATING : 0.5um MIN. Ni.
CONTACT AREA : 0.076 µm MIN. GOLD
SOLDER AREA : 2.5um MIN. Sn-Pb.
OR 2.5um MIN. PURE Sn.(FOR -XXXLF)
HOLD-DOWN : 2.5um MIN. PURE Sn.
5. RECOMMENDED PCB HOLE (OPTIONAL HOLD-DOWN) : 2.3±0.1
6. SEQUENCE PIN ASSIGNMENT

	DIM "L"		
	4.25±0.1	3.5±0.1	5.0±0.1
PIN No.	OTHERS	36.67	1.17.34 35.51.88


7. GENERAL TOLERANCE : ±0.3
8. SEE SHEET 1 REGARDING COMPONENTS.
9. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008


mat'l. code				surface ISO 1302		tolerance ISO 406 ISO 1101	projection	product family PCMCIA
ltr	ecn no	dr	date	tolerances unless otherwise specified				title
AM				angles	linear	0.X±0.3	MM	68 POS EJECTOR HEADER ASSY FOR 5.0V APPLICATION
				±2°		0.XX±0.13		
						0.XXX±0.051	scale	
				dr	Mike Zhou	11/21/06		dwg no 92140 sheet 5 of 7 size A4
				engr	Mike Zhou	11/21/06		
				chr	David Qin	11/21/06		
				appd	Jack Wang	11/21/06		type CUSTOMER Drawing
sheet index	revision sheet							


FCI CONFIDENTIAL
FCIconnect.com
This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.


form: A3


PRODUCT NO.		
92140-510	92140-510LF	92140-510HLF
92140-520	92140-520LF	
92140-520H	92140-520HLF	
92140-530	92140-530LF	
92140-540	92140-540LF	












DETAIL "Y" (5/1)



DETAIL "X" (20/1)
TYP(68)

NOTES
① TRUE POSITION IS A FREE GRID TO PIN PATTERN ITSELF.
2. SEE TA-946 FOR PCB LAYOUT.
③ MATERIAL
HOUSING : HIGH TEMPERATURE THERMOPLASTIC UL94V-0 BLACK
PIN : COPPER ALLOY.
HOLD-DOWN : BRASS
④ FINISH
PIN
UNDER PLATING : 0.5um MIN. Ni.
CONTACT AREA : 0.076 µm MIN. GOLD
SOLDER AREA : 2.5um MIN. Sn-Pb.
OR 2.5um MIN. PURE Sn.(FOR -XXXLF)
HOLD-DOWN : 2.5um MIN. PURE Sn.
5. RECOMMENDED PCB HOLE (OPTIONAL HOLD-DOWN) : 2.3±0.1
6. SEQUENCE PIN ASSIGNMENT

	DIM "L"		
PIN No.	4.25±0.1	3.5±0.1	5.0±0.1
	OTHERS	36.67	1.17,34 35,51,68

7. GENERAL TOLERANCE : ±0.3
8. SEE SHEET 1 REGARDING COMPONENTS.
9. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008

mat'l. code	surface	tolerance	projection	product family
	ISO 1302	ISO 406 ISO 1101		PCMCIA

ltr	ecn no	dr	date
AM			

tolerances unless otherwise specified

angles	linear	scale
±2°	0.X±0.3	MM
	0.XX±0.13	
	0.XXX±0.051	

dr	Mike Zhou	11/21/06	
engr	Mike Zhou	11/21/06	
chr	David Qin	11/21/06	
appd	Jack Wang	11/21/06	

title: 68 POS EJECTOR HEADER ASSY FOR 5.0V APPLICATION

dwg no: 92140 | sheet 6 of 7 | size A4

type: CUSTOMER Drawing

sheet index | revision sheet


This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI. Copyright FCI.


FCI CONFIDENTIAL

FCIconnect.com


form: A3

PRODUCT NO.
92140-505
92140-505LF
92140-535
92140-535LF
92140-545
92140-545LF







SECTION "Z"-"Z" (5/1)



DETAIL "Y" (5/1)





DETAIL "X" (20/1)
TYP(68)

NOTES
① TRUE POSITION IS A FREE GRID TO PIN PATTERN ITSELF.
2. SEE TA-946 FOR PCB LAYOUT.
③ MATERIAL
HOUSING : HIGH TEMPERATURE THERMOPLASTIC UL94V-0 BLACK
PIN : COPPER ALLOY.
HOLD-DOWN : BRASS
④ FINISH
PIN
UNDER PLATING : 0.5um MIN. Ni.
CONTACT AREA : 0.076 μm MIN. GOLD
SOLDER AREA : 2.5um MIN. Sn-Pb.
OR 2.5um MIN. PURE Sn.(FOR -XXXLF)
HOLD-DOWN : 2.5um MIN. PURE Sn.
5. RECOMMENDED PCB HOLE (OPTIONAL HOLD-DOWN) : 2.3±0.1
6. SEQUENCE PIN ASSIGNMENT

	DIM "L"		
	4.25±0.1	3.5±0.1	5.0±0.1
PIN No.	OTHERS	36.67	1,17,34 35,51,68

7. GENERAL TOLERANCE : ±0.3
8. SEE SHEET 1 REGARDING COMPONENTS.
9. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008
10. PRODUCT SPEC: 110-263

mat'l. code				surface	tolerance	projection	product family
				ISO 1302	ISO 406 ISO 1101		PCMCIA
ltr	ecn no	dr	date	tolerances unless otherwise specified			title
AM				angles	linear 0.X±0.3	MM	68 POS EJECTOR HEADER ASSY FOR 5.0V APPLICATION
				±2°	0.XX±0.13		
					0.XXX±0.051	scale	
				dr Mike Zhou 11/21/06			dwg no 92140 sheet 7 of 7 size A4
				engr Mike Zhou 11/21/06			
				chr David Qin 11/21/06			type CUSTOMER Drawing
				appd Jack Wang 11/21/06			
sheet index	revision sheet						

FCI CONFIDENTIAL
FCIconnect.com
This document is the property of and embodies CONFIDENTIAL and PROPRIETARY information of FCI. No part of the information shown on this document may be used in any way or disclosed to others without the written consent of FCI.
Copyright FCI.