953363-1 ✔ ACTIVE

MQS



TE Internal #: 953363-1

Vertical, Wire-to-Board, 6 Position, 2 Row, 2.54mm [.1in] Centerline, Tin (Sn), Printed Circuit Board, 7A Contact Current Rating (Max), Signal, Black

View on TE.com >

Automotive Parts > Automotive Connectors > Automotive Headers > Signal Header



PCB Mount Orientation: **Vertical**

Contact Current Rating (Max): **7 A**

Termination Method to PCB: **Through Hole - Solder**

Sealable: **No**

Centerline (Pitch): **2.54 mm [.1 in]**

All Signal Header (232)

Features

Product Type Features

Connector Product Type	Connector Assembly
Mixed & Hybrid Header	No
Header Type	Fully Shrouded
Connector Shape	Rectangular
Sealable	No
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Signal Positions	6
Number of Sections	1
PCB Mount Orientation	Vertical
Number of Positions	6
Number of Rows	2

Electrical Characteristics

Operating Voltage	12 VDC
Nominal Voltage Architecture	12 V

Body Features

Connector & Keying Code	1
Primary Product Color	Black

Contact Features

Mating Tab Width	.63 mm[.025 in]
Mating Tab Thickness	.63 mm[.025 in]
Contact Type	Tab
Contact Current Rating (Max)	7 A
Contact Mating Area Plating Material	Tin (Sn)

Termination Features

Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Panel Mount Feature	With
Mating Retention Type	Locking Interface
PCB Mount Retention	Without
Mounting Holes	With
Mating Alignment	With
PCB Mount Alignment	With
Connector Mounting Type	Panel Mount

Housing Features

Centerline (Pitch)	2.54 mm[.1 in]

Dimensions

Connector Width	16.5 mm[.65 in]
PCB Thickness (Recommended)	1.6 mm[.063 in]
Connector Length	22.8 mm[.898 in]
Profile Height from PCB	20.1 mm[.791 in]

Usage Conditions

Operating Temperature (Max)	65 °C, 70 °C, 75 °C, 80 °C, 85 °C[149 °F][158 °F][167 °F][176 °F][185 °F]

Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]

Operation/Application

Solder Process	Wave Solder Capable
Shielded	No
Circuit Application	Signal

Packaging Features

Packaging Quantity	1040
Packaging Method	Tray

Other

Interface Number	1379890

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




TE Part # 185311-1
6POS MQS REC

TE Part # 953362-3
6W MQS HSG STRAIGHT W EAR

TE Part # 953362-1
6W MQS HSG STRAIGHT W EAR

TE Part # 953362-4
6W MQS HSG STRAIGHT W EAR

Customers Also Bought



TE Part #282526-6
20P 070 MLK CAP HEAD ASSY



TE Part #CAT-SIGH262
Signal Header




TE Part #4-2176337-7
CRGCQ 0402 68K 1%




TE Part #2320201-1
MATENET,1-PORT,90DEG,HDR ASSY, COD A



TE Part #2321342-6
TAB0.5X0.4,NANO MS, NANOMULTISPRING INDIU



TE Part #2421721-6
21POS,TAB2.8X0.8,HDR ASSY,90DEG, COD A,RS



TE Part #7-6474621-9
FSN-22AB-6V2



TE Part #9-966658-2
32pos MQS .63 header 180deg

Documents

Product Drawings

6pos MQS .63 header 180deg

French

CAD Files

3D PDF

English

Customer View Model
ENG_CVM_953363-1_E.2d_dxf.zip

English

Customer View Model
ENG_CVM_953363-1_E.3d_igs.zip

English

Customer View Model
ENG_CVM_953363-1_E.3d_stp.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_953363-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_953363-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_953363-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Product Specification

English