BSCH001005055N6SCS

Aliases (CLH1005T-5N6S-S)

PULSE, BSCH, Multilayer, +/-0.3nH, 5,600 pH



General Information	
Series	BSCH
Style	SMD Multi-Layer
Core	Ceramic
RoHS	Yes

Dimensions	
L	1mm +/-0.10mm
W	0.5mm +/-0.1mm
T	0.5mm +/-0.1mm

Packaging Specifications	
Packaging	T&R
Packaging Quantity	10000

Specifications	
Inductance	5.6 nH
Inductance Tolerance	+/-0.3nH
Inductance	5,600 pH
Rated Current	400 mAmps (IDC)
Temperature Range	-55/+125°C
DC Resistance	200 mOhms
DC Resistance	0.2 Ohms
Quality Factor	8 at 100 MHz
Self-Resonant Frequency	5100 MHz

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

© 2006 - 2026 YAGEO