

	1	2	3	4	5	6	7	8	
F					REV.	ECN NO.	DATE	SIGN	DESCRIPTION
					A		2016/11/23	Victor Hung	Change Rev.01 To Rev.A
					B	C192027	2019/11/21	Vicky	X4
					C	C231238	2023/09/20	Vicky	X1
E									
					Sealing Nut Seal Clamp Ring Connector				
D					CD-XXBFMA-QL8XP0 07-7Pin 08-8Pin 09-9Pin S: With Red Color Seal 1, Cable OD 6.0~8.0mm. M: With Yellow Color Seal 2, Cable OD 8.0~10.0mm. L: With Blue Color Seal 3, Cable OD 10.0~12.0mm. A: With Seal 1 & Seal 2 & Seal 3.				
C									
B					Pin Assignments Front View 7 Pin 8 Pin 9 Pin				
A					UNIT:mm TOLERANCE $\pm 0.5\text{mm}$ TITLE XLOK, C-5A, CABLE W/O SR F, M, FI CRIMP, XLOK SCALE 1:1 SIZE A4 SHEET 1 OF 1 REV. C WC-REV. A.5 Inspection item Amphenol LTW 安費諾亮泰企業股份有限公司 ITEM NO DWG NO CUSTOMER ALTW DRAWN BY Victor Hung CHECKED BY Wes Fan APPROVED BY Kevin Hu DATE 2016-11-23 DATE 2016-11-23 DATE 2016-11-23				
	1	2	3	4	5	6	7	8	

Note:

- * Important Dimension
- * Waterproof Rate: IP68, Mated
IP68: 1M Depth Of Water In 24hours
- * Housing: Thermoplastic, Black
- * Pin: Copper Alloy, Gold Plated
- * Clamp Ring: Thermoplastic, Black
- * Sealing Nut: Thermoplastic, Black
- * Seals: Rubber
- * One set unassembled in one pe bag

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.