


CSSA8420

Automotive current sensing shunt resistor-high current



Applications

- Battery management systems (BMS)
- Power distribution units (PDUs)
- Electronic battery management (EBM) in automobiles, trucks, forklifts, hybrid and electric vehicles
- Junction boxes
- Bus bars
- Welding equipment


Product features

- AEC-Q200
- Resistance from 0.05 mΩ to 0.2 mΩ
- Low thermal EMF
- Low TCR
- 84.3 mm x 20.3 mm x 3.1 mm package
60 mm pitch
- High power ratings: up to 36 W
- Available with optional measuring pins


Environmental compliance



Table 1. Part numbering




Construction



Number	Materials
1	Copper electrode
2	MnCu
3	Measuring pin: tin plated copper

Dimension-mm



Family name and size	Resistance (mΩ)	L (mm)	W (mm)	A (mm)	C (mm)	D1 (mm)	E (mm)	T (mm)	For measuring pins only		
									B (mm)	D2 (mm)	H (mm)
CSSA8420	0.05	84.0 ± 0.3	20.0 ± 0.3	5.2 ± 0.3	60.0 ± 0.3	7.0 ± 0.3	2.3 ± 0.1	3.0 ± 0.1	8.0 ± 0.3	1.0 ± 0.1	11.0 ± 0.3
CSSA8420	0.1	84.0 ± 0.3	20.0 ± 0.3	10.0 ± 0.3	60.0 ± 0.3	7.0 ± 0.3	2.3 ± 0.1	3.0 ± 0.1	12.6 ± 0.3	1.0 ± 0.1	11.0 ± 0.3
CSSA8420	0.2	84.0 ± 0.3	20.0 ± 0.3	21.0 ± 0.3	60.0 ± 0.3	7.0 ± 0.3	2.3 ± 0.1	3.0 ± 0.1	24.0 ± 0.3	1.0 ± 0.1	11.0 ± 0.3

Recommended torque force

12N-m for M6

Electrical specifications


Part number	Power rating @ +125 °C (W)	Resistance ^b (mΩ)	Resistance tolerance	TCR ^a (ppm/°C)	Operating temperature	Measuring pins	Marking
CSSA8420M0L050FT0	36	0.05	±1%	±150	-55 °C to +170 °C	No	8420L050F
CSSA8420M0L10FT0	36	0.1	±1%	±150	-55 °C to +170 °C	No	8420L10F
CSSA8420M0L20FT0	24	0.2	±1%	±125	-55 °C to +170 °C	No	8420L20F
CSSA8420M2L050FT0	36	0.05	±1%	±150	-55 °C to +170 °C	2 Pins	8420L050F
CSSA8420M2L10FT0	36	0.1	±1%	±150	-55 °C to +170 °C	2 Pins	8420L10F
CSSA8420M2L20FT0	24	0.2	±1%	±125	-55 °C to +170 °C	2 Pins	8420L20F
CSSA8420M0L050JT0	36	0.05	±5%	±150	-55 °C to +170 °C	No	8420L050J
CSSA8420M0L10JT0	36	0.1	±5%	±150	-55 °C to +170 °C	No	8420L10J
CSSA8420M0L20JT0	24	0.2	±5%	±125	-55 °C to +170 °C	No	8420L20J
CSSA8420M2L050JT0	36	0.05	±5%	±150	-55 °C to +170 °C	2 Pins	8420L050J
CSSA8420M2L10JT0	36	0.1	±5%	±150	-55 °C to +170 °C	2 Pins	8420L10J
CSSA8420M2L20JT0	24	0.2	±5%	±125	-55 °C to +170 °C	2 Pins	8420L20J

a. Temperature coefficient of resistance tested at +25 °C to +125 °C

b. Resistance should be measured at +20 °C

Please contact technical support if there is any special requirement for resistance testing

Power derating curve



Rated current and voltage


The rated current and voltage are calculated by the following formulas:

$$I = \sqrt{P \div R} \quad V = \sqrt{P \times R}$$


I: Rated current (A) V: Rated voltage (V)

P: Rated power (W) R: Resistance value (Ω)


TCR curves



Maximum pulse power curve



Maximum pulse energy curve




General specifications

Item	Reference standard	Condition
Temperature coefficient of resistance test	MIL-STD-202 Method 304	$TCR = (R - R_0) / R_0 (T_2 - T_1) \times 10^6$ Test temperature: $T_1 = +25^\circ\text{C}$, $T_2 = +125^\circ\text{C}$
Short time overload	IEC 60115-1 4.13	5 times the rated power for 5 s, $ \Delta R \leq 1.0\%$
Solderability	J-STD-002	Solder bath method $(+245 \pm 5)^\circ\text{C}$ (10 ± 2) s (2 measuring pins only)
High temperature storage test	MIL-STD-202 Method 108	$+170^\circ\text{C}$ for 1000 hours, no power, $ \Delta R \leq 1.0\%$
Temperature cycling	JESD22 Method JA-104	-55°C (30 minutes) / $+155^\circ\text{C}$ (30 minutes), 1000 cycles, $ \Delta R \leq 1.0\%$
Temperature humidity bias test	MIL-STD-202 Method 103	$+85^\circ\text{C}$, 85% RH, 10% bias, 1000 hours, $ \Delta R \leq \pm 0.5\%$
Moisture resistance	MIL-STD-202 Method 106	No power, 7b not required, $ \Delta R \leq 1.0\%$
Operational life	MIL-STD-202 Method 108	$+125^\circ\text{C} \pm 2^\circ\text{C}$ for 1000 hours at rated power, $ \Delta R \leq 1.0\%$
Vibration	MIL-STD-202 Method 204	Frequency: 10 Hz to 2000 Hz, acceleration: 5 g's for 20 minutes, 12 cycles each of 3 orientations, $ \Delta R \leq \pm 0.5\%$
Mechanical shock test	MIL-STD-202 Method 213	100 g's, 6 ms, 5 pulses, $ \Delta R \leq \pm 0.5\%$
ESD	AEC-Q200-002 or ISO/DIS 10605	AEC-Q200-002, 25 kV, $ \Delta R \leq 1.0\%$
Electrical characterization	User spec	Rated power at -65°C , $+25^\circ\text{C}$ and $+125^\circ\text{C}$
Storage condition and shelf life	-	Temperature and humidity conditions: $+5^\circ\text{C}$ to $+30^\circ\text{C}$, 25% to 60% RH Shelf life is 2 years The products shall not be stored in areas where harmful gases containing sulfur or chlorine are present

Packaging information-mm

30 pieces per tray



L (mm)	W (mm)	A (mm)	T (mm)	H (mm)
335	335	83	2.60	28

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com/electronics

© 2024 Eaton
All Rights Reserved
Printed in USA
Publication No. ELX1441 BU-ELX22322
May 2024

Eaton is a registered trademark.

All other trademarks are property
of their respective owners.

Follow us on social media to get the
latest product and support information.

