

HDB36-24-16 P/SN

REVISIONS			
SYM	DESCRIPTION	DATE	APPROVED
N/C	NEW RELEASE PER E.O. 91285	6-8-81	T.H.

KEY, MAIN POLARIZING

INDICATOR, POLARIZING

1.530 MAX.

.085 MAX.

1.942φ MAX. OVER KNURL

1.477φ MAX.

.910 ±.015

PINS

SOCKETS

CABLE END VIEW OF CONNECTOR WITH INSERTS

3. THIS CONNECTOR SERIES WILL ACCOMMODATE THE FOLLOWING DIAMETERS.

CONTACT SIZE	MIN. O.D.	MAX. O.D.	WIRE GAGE RANGE
12	.134	.170	12 & 14

2. CONSULT FACTORY FOR ELECTRICAL AND MATERIAL SPECIFICATION.

1. PERTINENT INFORMATION: POWER CONTACTS
PIN 0460-204-12141 SOC. 0462-203-12141.

NOTE:

SIGNATURE & DATE		PLUG, CONNECTOR BREAKAWAY BAYONET COUPLING REAR INSERTION & REMOVAL ENVIRONMENTAL ENVELOPE	CP	MATL CODE	
DR	<i>[Signature]</i> 6-2-81		The Deutsch Company ELECTRONIC COMPONENTS DIVISION 8 Marina del Mar Airport Banning, California		
CHK	<i>[Signature]</i> 6-8-81		B	HDB36-24-16 P/SN	
PE	<i>[Signature]</i> 6-4-81			CODE 11139 SHEET 1 OF 1	
APPD					
SCALE	NONE	WT			