







F										
E										
D										
C										
B										
A										

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
I	C221878	2022/12/19	Ruru	XI
J	C231031	2023/08/04	Ruru	XI
K	C240700	2024/06/20	Ruru	X2

Note: C D F G H

- * RoHS Compliant
- * Important dimension
- * Waterproof rate: IP68, unmated 1m/24h
- * IP69K, mated
- * Connector
- Housing: Thermoplastic, Black
- Pin: Copper alloy, Gold plated
- * Shield: Metal
- * Nut: Metal
- * O-Ring: Rubber, Black
- * Wire harness: UL1061
- * For panel thickness max: 4.5mm
- * O-Ring and nut are assembled on connectors
- * Wire harness tolerance: 150mm < L ≤ 300mm: ±15mm
- 300mm < L ≤ 1000mm: ±20mm
- 1000mm < L ≤ 1500mm: +50/-0mm



Recommended Panel Cut-Out

UNIT: mm			TITLE N SEN, M12 A, SCREW RECEPTACLE, M, M, FI/PANEL CRIMP				Amphenol LTW			ITEM NO	DRAWN BY Ruru	DATE 2019-09-19
TOLERANCE	.X ±0.25	.XX ±0.1	SCALE 1:1	SIZE A4	SHEET 1 OF 2		安費諾亮泰企業股份有限公司			DWG. NO MI2A-XXPMC-SH8BXX	CHECKED BY Rita	DATE 2019-09-19
ANGLES	.XXX ±1°		REV. K	WC-REV. A.5	QC: Inspection item					CUSTOMER ALTW	APPROVED BY Max	DATE 2019-09-19

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

W10814-03-0001A2

