NT-MIL-1/2-0-SP ✔ ACTIVE


RAYCHEM

TE Internal #: C32412-000

Heat Shrink Tubing, Black, 1.75:1, Single Wall, Shrinks To 7.3 mm [.287 in], Chlorinated Polyolefin, 12.7 mm [.5 in] Expanded Inside, Flame-Retardant

View on TE.com >

Heat Shrink Tubing > Single Wall NT MIL: Heat Shrink Tubing, 1.75:1 Shrink Ratio



Tubing Product Type: **Heat Shrink Tubing**

Primary Product Color: **Black**

Wall Type: **Single Wall**

Expanded Inside Diameter (Min): **12.7 mm [.5 in]**

Recovered Inside Diameter (Max): **7.3 mm [.287 in]**

All Single Wall NT MIL: Heat Shrink Tubing, 1.75:1 Shrink Ratio (0)

Features

Product Type Features

Tubing Product Type	Heat Shrink Tubing
Wall Type	Single Wall

Body Features

Material Systems Code	20
Fluid Type	Aviation Fuel, Chemicals/Solvents, Ground Vehicle Fuels, Hydraulic Fluid, Lubricating Oil, Water
Primary Product Color	Black
Shrink Ratio	1.75:1
Primary Product Material	Chlorinated Polyolefin
Flexibility	Flexible

Dimensions

Recovered Wall Thickness (Nominal)	1.21 mm[.048 in]
Expanded Inside Diameter (Min)	12.7 mm[.5 in]
Recovered Inside Diameter (Max)	7.3 mm[.287 in]
Tubing Size Range	7.3 – 12.7 mm[.287 – .5 in]

Usage Conditions

Shrink Temperature (Min)	135 °C
Tubing Flammability Type	Flame-Retardant
Operating Temperature Range	-70 – 121 °C[-94 – 249.8 °F]
Recovery Temperature	135 °C

Operation/Application

Mechanical Resistance	Abrasion, Fluids, Mechanical Damage, Strain Relief

Product Availability

Applicable Region	Worldwide

Packaging Features

Packaging Method	Piece

Other

Meets Low Outgassing Requirements	No
Product Source	US

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides

on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Customers Also Bought



TE Part #NB18994001
RNF-100-1/4-CL-SP




TE Part #CB5036-000
BSTS-13X4



TE Part #32151
SPLICE,SOLIS BUTT 12-10



TE Part #350980-3
.045 POST CONTACT AUPLBR



TE Part #608802-1
CABLE TIE MOUNT, 4-WAY,3/4" SQ



TE Part #3-640427-5
05P MTA156 CONN ASSY 20AWG YEL




TE Part #1-794612-2
PIN CONT 20-24 30 GOLD L/P



TE Part #8-1437627-2
G12B=BUTTON GUARD BLACK



TE Part #1-1546406-1
ETHERNET CLOSURE CAP RECPT W /LANYRD



TE Part #1825851-1
AMPMODU MOD IV LATCH for AMPLA

Documents

Product Drawings

NT-MIL-1/2-0-SP

English

Datasheets & Catalog Pages

1654025_Sec3_NT-MIL

English

Flexible, Rugged, Modified Elastomeric Heat-Shrinkable Tubing

English

Product Specifications

Raychem NT-MIL Tubing Modified Chlorinated Polyolefin, Elastomeric, Flexible, Flame Retarded, Heat-Shrinkable

English

Heat Shrink Tubing, Black, 1.75:1, Single Wall, Shrinks To 7.3 mm [.287 in], Chlorinated Polyolefin, 12.7 mm [.5 in] Expanded Inside, Flame-Retardant