


REVISIONS			
REV	DESCRIPTION, ECN, EAR NO.	DATE	APP'D
A	PROPOSAL PER EAR# RJ19019	MAR06/19	L.CHAN




FRONT VIEW




SIDE VIEW



BACK VIEW



RECOMMENDED P.C.B. LAYOUT
(COMPONENT SIDE OF BOARD)



RECOMMENDED PANEL LAYOUT



MATERIALS:

HOUSING: ENGINEERING THERMOPLASTIC.
FLAMMABILITY RATING UL 94V–0, COLOUR: BLACK

CONTACTS: PHOSPHOR BRONZE
PLATING: REFER TO PART NUMBER FOR GOLD THICKNESS ON MATING SURFACE.
50µ" [1.27 MICRONS] MIN. NICKEL UNDERPLATE.
100µ" MIN. MATTE TIN OR GOLD FLASH ON CONTACT AILS.

SHIELD: COPPER ALLOY
PLATING: NICKEL WITH TIN DIPPED PCB TAILS.

RECOMMENDED SOLDERING TEMPERATURE:
WAVE SOLDERING AT 260°C AT 260°C MAXIMUM FOR 5 SEC MAXIMUM.


PART NUMBER: RJSAE–X380–A4

GOLD PLATING
5 = 50 u" GOLD
J = 30 u" GOLD
G = 15 u" GOLD
D = 6 u" GOLD

UNLESS SPECIFIED OTHERWISE	DRAWN RONNIE.C	MAR06/19	Amphenol Canada Corp. Commercial Products
PRIMARY UNITS INCHES	CHECKED L.CHAN	MAR06/19	
SECONDARY MILLIMETERS	M.E. APP'D		STACKABLE MULTI–PORT MODULAR JACK SHIELDED, 4 PORT, 2 PIECE CONSTRUCTION 8 POSITION, 8 CONTACTS, WITHOUT LEDS, 0.130 INCH CONTACT TAILS–RoHS COMPLIANT
REFERENCE IN PARENTHESES	Q.A. APP'D		
GENERAL TOLERANCES	DWG APP'D		
1 DECIMAL PLACE ±.025	ENG. REL. NO.		
2 DECIMAL PLACES ±.020	REF. EAR#: RJ19019		DWG NO. P-RJSAE-X380-A4 REV A
3 DECIMAL PLACES ±.015	THIRD ANGLE PROJECTION	DO NOT SCALE DRAWING	CODE ID NO. 03554 DWG SIZE X SCALE XX:1 SHEET 1 OF 2
ANGULAR DEGREES ±1.5°			


THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM AMPHENOL CANADA CORP.

REVISIONS			
REV	DESCRIPTION, ECN, EAR NO.	DATE	APP'D
A	PROPOSAL PER EAR# RJ19019	MAR06/19	L.CHAN



CONNECTOR


CONNECTOR PLACE INTO FOAM



25PCS CONNECTOR PER FOAM


AMPHENOL CANADA CORP
RoHS COMPLIANT
2011/65/EU RECAST

6 PIZZA BOX IN CARTON




LABEL

SEAL THE CARTON



PLACE FOAM INSERT
INTO PIZZA BOX



NOTES:

PACAKING QUANTITY
1. 25PCS PER FOAM
2. 6 PCS PIZZA BOX PER CARTON
   150 PCS CONNECTORS PER CARTON

UNLESS SPECIFIED OTHERWISE	DRAWN RONNIE.C	MAR06/19	Amphenol Canada Corp. Commercial Products
PRIMARY UNITS INCHES	CHECKED L.CHAN	MAR06/19	
SECONDARY MILLIMETERS	M.E. APP'D		STACKABLE MULTI-PORT MODULAR JACK SHIELDED, 4 PORT, 2 PIECE CONSTRUCTION 8 POSITION, 8 CONTACTS, WITHOUT LEDS, 0.130 INCH CONTACT TAILS-RoHS COMPLIANT
REFERENCE IN PARENTHESES	Q.A. APP'D		
GENERAL TOLERANCES	DWG APP'D		
1 DECIMAL PLACE ±.025	ENG. REL. NO.		
2 DECIMAL PLACES ±.020	REF. EAR#: RJ19019		DWG NO. P-RJSAE-X380-A4 REV A
3 DECIMAL PLACES ±.015	THIRD ANGLE PROJECTION	DO NOT SCALE DRAWING	CODE ID NO. 03554 DWG SIZE X SCALE XX:1 SHEET 2 OF 2
ANGULAR DEGREES ±1.5°			

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM AMPHENOL CANADA CORP.