


REVISIONS			
REV	DESCRIPTION, ECN, EAR NO.	DATE	APP'D
A	PROPOSAL	MAY 21/18	L.CHAN
B	CORRECTED SIDE VIEW	MAY 23/18	L.CHAN
C	CORRECTED LED TAILS	MAY 30/18	L.CHAN
D	MODIFY PANEL LAYOUT	JUN 01/18	L.CHAN




FRONT VIEW




SIDE VIEW




BACK VIEW




RECOMMENDED P.C.B. LAYOUT
(COMPONENT SIDE OF BOARD)
TOLERANCE: ±0.05 [.002]




RECOMMENDED PANEL LAYOUT





BI-COLOUR LED DETAIL

(GREEN/YELLOW, RED/YELLOW AND
GREEN/ORANGE ARE ALSO AVAILABLE)



LED SCHEMATIC

MATERIALS:

HOUSING: ENGINEERING THERMOPLASTIC
FLAMMABILITY RATING UL 94V-0, BLACK.

CONTACTS: PHOSPHOR BRONZE
PLATING: SELECTIVE GOLD PLATING ON MATING SURFACES
SEE AMPHENOL PART NUMBER FOR DETAIL.
50µ" [1.27 MICRONS] MIN. NICKEL UNDERPLATE.
100µ" MIN. MATTE TIN OR GOLD FLASH ON CONTACT AILS.

SHIELD: COPPER ALLOY
PLATING: NICKEL WITH TIN DIPPED TAILS.

RECOMMENDED SOLDERING TEMPERATURE:
WAVE SOLDERING AT 260°C MAXIMUM FOR 5 SEC MAXIMUM.

AMPHENOL PART NUMBER: RJSAE-XF8X-A4X


GOLD PLATING OPTION:
D = 6 u" GOLD PLATING
G = 15u" GOLD PLATING
J = 30u" GOLD PLATING
5 = 50u" GOLD PLATING

REFER TO LED OPTIONS DRAWING
FOR ORDERING CODES

UNLESS SPECIFIED OTHERWISE	DRAWN HANSON.C	DATE MAY 21/18	Amphenol Canada Corp. Commercial Products
PRIMARY UNITS INCH	CHECKED AMY.Z	MAY 21/18	
SECONDARY MILLIMETER	M.E. APP'D		TITLE: STACKABLE MULTI-PORT MODULAR JACK, SHIELDED, 4 PORTS, 2 PIECE CONSTRUCTION(8 POSITION, 8 CONTACTS, WITH LEDS) - RoHS COMPLIANT
REFERENCE IN PARENTHESES	Q.A. APP'D		
GENERAL TOLERANCES	DWG APPR.		
1 DECIMAL PLACE ±0.025	ENG. REL. NO.		
2 DECIMAL PLACES ±0.020	REF. EAR#: RJ18107		DWG. NO. P-RJSAE-XF8X-A4X REV D
3 DECIMAL PLACES ±0.015	THIRD ANGLE PROJECTION	DO NOT SCALE DRAWING	CODE ID NO. 03554 DWG SIZE: C SCALE: N/A SHEET 1 OF 3
ANGULAR DEGREES ±1.0°			


THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM AMPHENOL CANADA CORP.

REVISIONS			
REV	DESCRIPTION, ECN, EAR NO.	DATE	APP'D
A	PROPOSAL	MAY 21/18	L.CHAN
B	CORRECTED SIDE VIEW	MAY 23/18	L.CHAN
C	CORRECTED LED TAILS	MAY 30/18	L.CHAN
D	MODIFY PANEL LAYOUT	JUN 01/18	L.CHAN




CONNECTOR

CONNECTOR PLACE INTO FOAM




25PCS CONNECTOR PER FOAM

6 PIZZA BOX IN CARTON




LABEL

SEAL THE CARTON



PLACE FOAM INSERT
INTO PIZZA BOX



AMPHENOL CANADA CORP
RoHS COMPLIANT
2011/65/EU RECAST


NOTES:

PACAKING QUANTITY
1. 25PCS PER FOAM
2. 6 PCS PIZZA BOX PER CARTON
   150 PCS CONNECTORS PER CARTON

UNLESS SPECIFIED OTHERWISE	DRAWN HANSON.C	DATE MAY 21/18	Amphenol Canada Corp. Commercial Products
PRIMARY UNITS INCH	CHECKED AMY.Z	MAY 21/18	
SECONDARY MILLIMETER	M.E. APP'D		TITLE STACKABLE MULTI-PORT MODULAR JACK, SHIELDED, 4 PORTS, 2 PIECE CONSTRUCTION(8 POSITION, 8 CONTACTS, WITH LEDS) – RoHS COMPLIANT
REFERENCE IN PARENTHESES	Q.A. APP'D		
GENERAL TOLERANCES	DWG APPR.		
1 DECIMAL PLACE ±0.025	ENG. REL. NO.		
2 DECIMAL PLACES ±0.020	REF. EAR#: RJ18107		DWG. NO. P-RJSAE-XF8X-A4X REV D
3 DECIMAL PLACES ±0.015	THIRD ANGLE PROJECTION	DO NOT SCALE DRAWING	CODE ID NO. 03554 DWG SIZE: C SCALE: N/A SHEET 2 OF 3
ANGULAR DEGREES ±1.0°			

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM AMPHENOL CANADA CORP.

REVISIONS			
REV	DESCRIPTION, ECN, EAR NO.	DATE	APP'D
H	PROPOSAL	JUL 04/12	L.CHAN
J	PROPOSAL	MAR 03/14	L.CHAN
K	ADD NEW COLOR OPTION	FEB 09/17	L.CHAN



TYPICAL FOR TWO & MULTI-PORT

+ — (ANODE)+ —(CATHODE)

LED SPECIFICATIONS:
FORWARD VOLTAGE: 2.1 VOLTS TYP.
REVERSE VOLTAGE: 5.0 VOLTS MIN.
LUMINOUS INTENSITY: 0.5 mCd MIN.
(AT If=2mA)
STORAGE TEMPERATURE: -20° TO 85° C
PLATING ON TAILS: TIN OR TIN/COPPER ALLOY OVER SILVER

EXAMPLE:1
PART NUMBER RJSAE-***X-**
SEE NOTE 2
SEE NOTE 2
LED COLOR CODE

EXAMPLE:2
PART NUMBER RJSAE-***U-**-XX
SEE NOTE 2
BOTTOM ASSY LED (SAME AS STD CODE)
SPECIAL CODE FOR TOP & BOTTOM LEDS CONFIGURATION
TOP ASSY LED (SAME AS STD CODE)
SEE NOTE 2

CODE	LED 2 (LEFT)	LED 1 (RIGHT)	CODE	LED 2 (LEFT)	LED 1 (RIGHT)	CODE	LED 2 (LEFT)	LED 1 (RIGHT)
0	BLOCKED	BLOCKED	9	GREEN	BLOCKED	J	BiC RD/GR	YELLOW
1	YELLOW	GREEN	A	BiC GR/YE	BiC GR/YE	K	YELLOW	BiC GR/OR
2	BLOCKED	GREEN	B	BiC RD/GR	BiC RD/GR	L	BiC GR/YE	RED
3	YELLOW	BLOCKED	C	BiC RD/GR	BiC GR/YE	M	RED	YELLOW
4	GREEN	YELLOW	D	GREEN	BiC GR/YE	N	BiC GR/RD	BiC GR/YE
5	GREEN	GREEN	E	YELLOW	BiC GR/YE	P	GREEN	BiC RD/GR
6	YELLOW	YELLOW	F	BiC GR/YE	YELLOW	R	BiC GR/OR	GREEN
7	RED	GREEN	G	BiC GR/OR	BiC GR/OR	T	RED	RED
8	GREEN	RED	H	BiC GR/YE	GREEN	V	BiC RD/GR	GREEN
						W	ADDITIONAL OPTIONS	
						U	SPECIAL CODE FOR TOP & BOTTOM LEDS CONFIGURATION	

EXAMPLE:3
PART NUMBER RJSAE-***W-**X
SEE NOTE 2
ADDITIONAL LED COLOR CODE
SEE NOTE 2
DENOTES ADDITIONAL LED OPTIONS TO BE USED

CODE	LED 2 (LEFT)	LED 1 (RIGHT)	CODE	LED 2 (LEFT)	LED 1 (RIGHT)	CODE	LED 2 (LEFT)	LED 1 (RIGHT)
0	DO NOT USE		5	BLOCKED	YELLOW	A	LOWC YE	LOWC YE
1	RED	BLOCKED	6	RED	BiC RD/GR	B	LOWC YE	LOWC GR
2	BiC GR/OR	YELLOW	7			C	LOWC GR	LOWC YE
3	YELLOW	RED	8	BiC RD/GR	BLOCKED	D	LOWC GR	LOWC GR
4	BLOCKED	RED	9	BiC GR/YE	BLOCKED	M	LOWC RD	LOWC YE
						N	GREEN	BiC GR/OR
						E	GREEN	ORANGE
						F	ORANGE	GREEN
						G	BiC YE/GR	BiC YE/GR
						P	BiC RD/YE	GREEN
						R	BiC RD/YE	BiC RD/YE
						T	BiC GR/YE	BiC RD/GR
						H	BLUE	RED

EXAMPLE:4
PART NUMBER RJSAE-***X-**XX*
SEE NOTE 2
LED COLOR CODE THE SAME AS EXAMPLE 1, 2, 3
SEE NOTE 2
LED COLOR CODE THE SAME AS EXAMPLE 1, 2, 3
SEE NOTE 2

PRIMARY COLOR FOR BI-COLOR LEDS IN STANDARD ANODE/CATHODE CONFIGURATION IS:
RED-GREEN= RED
RED-YELLOW= RED
GREEN-YELLOW= GREEN
GREEN-ORANGE= GREEN

LEGEND
BiC=BI-COLOR LED
LOWC=LOW CURRENT LED
YE=YELLOW
GR=GREEN
RD=RED
OR=ORANGE

AMPHENOL CANADA CORP
RoHS COMPLIANT
2011/65/EU RECAST

NOTES:
1. THE TWO DIGITS PRECEDING THE ADDITIONAL LED CODE MUST BE USED IN THE PART NUMBER, WHEN ORDERING ANY OF THE ADDITIONAL LED OPTIONS.
2. '*' REPRESENT DIFFERENT OPTION OF CONNECTOR, DETAIL OPTION PLEASE SEE RELEVANT CONNECTOR DRAWING.

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM AMPHENOL CANADA CORP.

UNLESS SPECIFIED OTHERWISE	DRAWN PAUL WANG	DATE JUL 22/05	Amphenol Canada Corp. www.amphenolcanada.com
PRIMARY UNITS	CHECKED LAWRENCE C	JUL 22/05	
SECONDARY	M.E. APP'D		TITLE: LED OPTIONS FOR RJSAE, MULTI-PORT CONNECTORS - RoHS COMPLIANT
REFERENCE IN PARENTHESES	Q.A. APP'D		
GENERAL TOLERANCES	DWG APPR.		
1 DECIMAL PLACE	ENG. REL. NO.		DWG. NO. P-RJSAE-LEDS REV K
2 DECIMAL PLACES	REF.		
3 DECIMAL PLACES	THIRD ANGLE PROJECTION	DO NOT SCALE DRAWING	CODE ID NO. 03554 DWG SIZE: C SCALE: N/A SHEET 1 OF 1
ANGULAR DEGREES			