



REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A	Initial Release	2017/07/27	Lingpeng	New Item.
B	LEN17A0097~112	2017-10-14	Lingpeng	Add The Label And Change The Title
C	N180019	2019-03-14	Lingpeng	Add All Seals Product






ALTW
CONFIDENTIAL
2019-03-14
R&D DEPT.








UNIT: mm	TITLE: B ULI3 Cable Joiner Screw-in Type		
TOLERANCE ±0.5mm	SCALE 1:1	SIZE A4	SHEET 1 OF 2
	REV. C	WC-REV. A.3	QC: Inspection item


Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO		DRAWN BY Lingpeng	DATE 2019-03-14
DWG NO SC-L-ULI3-XX-XX		CHECKED BY MaFei	DATE 2019-03-14
CUSTOMER ALTW		APPROVED BY Jerry	DATE 2019-03-14


THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.



QTY: 1PCS



QTY: 105PCS



ALTW
CONFIDENTIAL
2019-03-14
R&D DEPT.

Both A Unassembled product And An Instruction Are In A PE Bag.
（將一套未組裝的產品和說明書，放置於一個PE袋，並封口）

SC-L-UL13-XX-XX

- L:Cable Joiner
- Type: UL13
- No. of Condutor: 02-2Poles, 03-3Poles, 04-4Poles, 05-5Poles
- Seal's Color: (C)

BL-Blue(藍色)	For Cable Range:	Ø4.5~Ø6.5mm
YW-Yellow(黃色)	For Cable Range:	Ø6.5~Ø8.5mm
GN-Green(綠色)	For Cable Range:	Ø8.5~Ø10.5mm
RD-Red(紅色)	For Cable Range:	Ø10.5~Ø11.5mm
AA-All Seals	For Cable Range:	Ø4.5~Ø11.5mm

Note:
* (QC) Important Dimension To Check.
* Waterproof Rate: IP68 (50M,24H)
* Housing & Cap: PA66+GF, Black.
* Gland Pipe: PA66, Black.
* Gland Body: PA66, Black.
* Gland Nut: PA66, Black.
* Contact: Brass, Nickel Plated
* L-Gasket : Silicone, Yellow.
* Seal: Silicone, Blue & Yellow & Green & Red.
* Rated Voltage: 2~5 Pole 600V AC
* Rated Current: 2 & 3 Pole Max. 20A ,
  4 Pole Max. 15A.
  5 Pole Max. 8A.
* Operating Temperature: -40°~+105°.
* Gland Pipe Recommended Tightening Torque: 8~10 Kgf.cm(0.78~0.98 N.m)
* Gland Nut Recommended Tightening Torque: 8~10 Kgf.cm(0.78~0.98 N.m)
* Seal For Cable OD: Ø4.5~Ø6.5mm, Blue.
  Ø6.5~Ø8.5mm, Yellow.
  Ø8.5~Ø10.5mm, Green .
  Ø10.5~Ø11.5mm, Red.
* Screws for Wire connection recommended tightening torque: 2.00~4.50 kgf.cm / 0.196~0.44 N.m
* Applicable Wire gauge: 18AWG~12AWG(2~4 pole)
  18AWG~14AWG(5 pole)
* UL2238 Certification


Pole Assignments Front View




2 Pole



3 Pole



4 Pole



5 Pole

UNIT: mm

TOLERANCE ±0.5mm

TITLE: B UL13 Cable Joiner Screw-in Type

SCALE 1:1 | SIZE A4 | SHEET 2 OF 2

REV. C | WC-REV. A.3

(QC): Inspection item

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO		DRAWN BY: Lingpeng	DATE: 2019-03-14
DWG NO: SC-L-UL13-XX-XX		CHECKED BY: MaFei	DATE: 2019-03-14
CUSTOMER: ALTW		APPROVED BY: Jerry	DATE: 2019-03-14

WI0814-03-RW01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.