Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: TLP6B

6 outlet, 6-ft cord, 360 joules Protect It! Surge Suppressor



Highlights

- 6 outlet / 6-ft cord
- 360 joule rating
- $10,000 Ultimate Lifetime Insurance (US & Canada only)

Description

Tripp Lite's TLP6B offers economical AC surge suppression for protection of workstations, desktop PC's, telecom systems and other sensitive electronics. Built-in AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLP6B offers 6 total outlets, 6 foot cord and diagnostic LED to warn of suppressor damage. AC suppression rated at 360 joules shields equipment from surges and line noise. Attractive black suppressor housing with keyhole mounting tabs offer convenient protection of desktop computer equipment and accessories. $10,000 Ultimate Lifetime Insurance (US & Canada only).
PLUG/OUTLETS: Input: NEMA5-15P / Output: 6 NEMA5-15R / 6-ft AC line cord
ELECTRICAL: 120V AC, 60Hz, 15A (Requires NEMA5-15R wall receptacle)
FORMAT: Corded multi-outlet strip with 1 transformer spaced outlet
SUPPRESSION: AC: 150V RMA Clamping / 360 joules/ 500V UL1449 3rd Edition

Applications

- Ideal for any desktop, network or home computing application requiring AC line protection

Package Includes

- TLP6B surge suppressor

Features

- 6 outlets
- 6-ft cord
- Surge suppression rating: 360 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker
- Green "Protected" LED
- Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- Can accommodate 1 large transformer plug without covering remaining outlets, 3 total transformers
- Keyhole support for wall mounting
- Lighted power switch
- $10,000 Ultimate Lifetime Insurance (US & Canada only)
- Lifetime product warranty

Specifications

OVERVIEW	

Intended Application	Home / Office
OUTPUT	
Frequency compatibility	60 Hz
Output watts	1875
Circuit Breaker (amps)	15
Overload protection	15A resettable illuminated combo switch / circuit breaker
Outlet quantity / type	6 NEMA 5-15R
Transformer accommodation	Supports 1 large transformer plug accessory without blocking remaining outlets, accepts up to 3 transformers total
Outlet orientation	Single row of 6 outlets
INPUT	
Recommended Electrical Service	120V (110-125V)
Input connection type	NEMA 5-15P
Input cord length (ft.)	6
Input cord gauge, type	14 gauge, SJT
Voltage compatibility (VAC)	120
LEDS ALARMS & SWITCHES	
Switches	Combination AC circuit breaker and 2 position red illuminated on/off power switch
Diagnostic LEDs	Built-in LED confirms suppressor "protection present" (green) status
SURGE / NOISE SUPPRESSION	
AC suppression joule rating	360
AC suppression response time	< 1 ns
Protection modes	L-N
Clamping voltage (RMS)	150
UL1499 let through rating	500v
EMI / RFI filtering	up to 20dB
DATALINE SURGE SUPPRESSION	
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
PHYSICAL	
Shipping weight (lbs)	.86
Unit Dimensions (HWD/in)	11.25 x 3.77 x 1.10
Shipping Dimensions (HWD/in)	9.21 x 3.77 x 1.10
Unit weight (lbs)	.81

Material of construction	Plastic
Integrated keyhole mounting tabs	Keyhole mounting tabs enable wall mounting
Receptacle Color	Black
AC line cord color	Black
Style	Strip
CERTIFICATIONS	
Additional International Approvals	RoHS
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition
UL1363 (Power Tap)	UL1363
cUL / CSA (Canada)	cUL
Approvals	Exceeds IEEE 587 category A&B specifications
WARRANTY	
Product Warranty Period (U.S., Canada & Puerto Rico)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	$10,000 Ultimate Lifetime Insurance

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=5020.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.