Honeywell | Sensing and Control

# WW1A24A-D8






Actual product appearance may vary.

**WW Series Snap-in Panel Mount Switch, Single Pole Normally Closed (SPNC) Circuitry, 3 A at 125 Vac, Plunger Lever, Quick Connect Termination**

## Product Specifications

| | |
|---|---|
| Switch Type | Snap-in Panel Mount (13,97 mm x 28,45 mm [0.55 in x 1.12 in] panel cutout) |
| Sealed | No |
| Ampere Rating | 3 A |
| Circuitry | SPNC |
| Actuator | Plunger Lever |
| Termination | Quick Connect |
| Voltage | 125 Vac |
| Actuator Length | 12,5 mm [.49 in] |
| Overtravel (OT) | 5,0 mm [0.20 in] min. |
| Operating Position (OP) | 3,5 mm [0.14 in] |
| Material | Plastic |
| Housing Material | Plastic |
| Expected Mechanical Life | 100000 cycles |
| Agency Approvals and Standards | UL, CSA |
| Package Height | 40,00 mm [1.575 in] |
| Package Width | 31,52 mm [1.241 in] |
| Package Length | 17,53 mm [0.69 in] |
| Recommended For | Door Status Indication |
| Availability | Global |
| UNSPSC Code | 39122209 |
| UNSPSC Commodity | 39122209 Snap switches |
| Series Name | WW |