
High Precision Bulk Metal® Foil Molded Surface Mount Resistor

with TCR down to ±2 ppm/°C, Flexible Terminations, and Load Life Stability of ±0.005% (50 ppm)

FEATURES

- Temperature coefficient of resistance (TCR): ±2 ppm°C typical (–55°C to +125°C, +25°C ref.)
- Tolerance: to ±0.01%
- Flexible terminations ensure minimal stress transference from the PCB due to a difference in thermal coefficient of expansions (TCE)
- Load life stability: ±0.005% (70°C, 2000 h at rated power)
- Resistance range: 5 Ω to 80 kΩ
- Power rating: to 600 mW at 70°C
- Non inductive, non capacitive design





Pb-free Available


RoHS* COMPLIANT

Tolerance and TCR Vs. Resistance Value
(–55°C to +125°C, +25°C Ref.)

VALUE	STANDARD TOLERANCE(1)	TYPICAL TCR AND MAX. SPREAD(1) (ppm/°C)
50 Ω to 80 kΩ	±0.01%	±2±3
20 Ω to <50 Ω	±0.02%	±2±4
10 Ω to <20 Ω	±0.05%	±2±6
5 Ω to <10 Ω	±0.1%	±2±8

Note
(1) Tighter performances are available

Power Derating Curve



The SMRXD Series is Listed in the Following DSCC Specifications

MODEL	DSCC	MIL SPEC
SMR1D	06020	MIL-PRF-55182
SMR3D	06021	MIL-PRF-55182

The document and the products described herein are subject to change from time to time without notice and are also subject to specific disclaimers. Please visit https://vpgsensors.com/disclaimer for more information.

Performance Specifications


TEST	CONDITIONS				MAXIMUM LIMIT[1]	
	SMR1D		SMR3D		SMR1D	SMR3D
Resistance Range					5 Ω to 33 kΩ	5 Ω to 80 kΩ
Rated Power	5 Ω to 10 kΩ 0.250 W at 70°C 0.125 W at 125°C	10 kΩ to 33 kΩ 0.160 W at 70°C 0.08 W at 125°C	5 Ω to 30 kΩ 0.6 W at 70°C 0.3 W at 125°C	30 kΩ to 80 kΩ 0.4 W at 70°C 0.2 W at 125°C		
Maximum Working Voltage					73 V	180 V
Maximum Operating Temperature	+175°C					
Working Temperature Range	–55°C to +125°C (MIL range)					
Thermal Shock	–65°C to +150°C; 30 min; 5 cycles				±0.01% (100 ppm)	
Short Time Overload	6.25 x rated power; 5 s				±0.01% (100 ppm)	
Low Temperature Storage	24 h at –65°C				±0.01% (100 ppm)	
Low Temperature Operation	45 min, rated power at –65°C				±0.01% (100 ppm)	
Dielectric Withstanding Voltage	atmospheric pressure; AC 200 V; 1 min				±0.01% (100 ppm)	
Insulation Resistance (MΩ)	DC 100 V; 1 min				over 10 000	
Resistance to Soldering Heat (%)	260°C; 10 s				±0.02%, ±0.01% typical	
Moisture Resistance	+65°C to –10°C; 90% to 98% RH; rated power; 240 h				±0.02% (200 ppm)	
Shock	100 G; sawtooth				±0.01% (100 ppm)	
Vibration, High Frequency	10 ~ 2000 ~ 10 Hz; 20 G; Y, Z each 4 h				±0.01% (100 ppm)	
Load Life Stability (2000 h)	0.04 W at +70°C 0.25 W at +70°C 0.125 W at +125°C		0.1 W at +70°C 0.6 W at +70°C 0.3 W at +125°C		Typical 0.005% 0.02% 0.02%	Typical 0.005% 0.015% 0.015%
High Temperature Exposure	175°C; no load 2000 h				±0.05% (500 ppm)	
Weight					0.1143 g	0.244 g
Packaging	bulk (loose) or tape and reel, per EIA-481-1					

Note

(1) As shown +0.01 Ω to allow for measurement error at low values


The document and the products described herein are subject to change from time to time without notice and are also subject to specific disclaimers. Please visit https://vpgsensors.com/disclaimer for more information.

Dimensions in inches (millimeters)



MODEL	L	W	H	P	TW	TH (minimum)
SMR1D	0.236±0.012 (5.99±0.30)	0.126±0.012 (3.20±0.30)	0.098±0.012 (2.49±0.30)	0.051±0.012 (1.30±0.30)	0.087±0.004 (2.21±0.10)	0.039 (0.99)
SMR3D	0.287±0.012 (7.29±0.30)	0.170±0.012 (4.32±0.30)	0.110±0.012 (2.79±0.30)	0.051±0.012 (1.30±0.30)	0.095±0.004 (2.41 ±0.10)	0.039 (0.99)

Recommended Mounting Pad Geometries in inches (millimeters)




MODEL	METHOD	A MIN.	B REF	C REF	D ±0.04 (±1.02)	E REF
SMR1D	Reflow	0.110 (2.79)	0.106 (2.69)	0.124 (3.15)	0.337 (8.55)	0.050 (1.27)
SMR3D	Reflow	0.118 (3.00)	0.106 (2.69)	0.175 (4.45)	0.388 (9.86)	0.050 (1.27)
Per IPC-SM-782 Rev. A						

The document and the products described herein are subject to change from time to time without notice and are also subject to specific disclaimers. Please visit https://vpgsensors.com/disclaimer for more information.

Global Part Number Information


NEW GLOBAL PART NUMBER : Y112110K0000T9R (preferred part number format)



FOR EXAMPLE: ABOVE GLOBAL ORDER Y1121 10K0000T 9R:

TYPE: SMR1D
VALUE: 10.0kΩ
ABSOLUTE TOLERANCE: ±0.01%
TERMINATION: lead (Pb)-free
PACKAGING: tape and reel

HISTORICAL PART NUMBER : SMR1D 10K000 TCR2 T S T (will continue to be used)



Note
* For non-standard requests, please contact application engineering.

The document and the products described herein are subject to change from time to time without notice and are also subject to specific disclaimers. Please visit https://vpgsensors.com/disclaimer for more information.