Honeywell | Sensing and Control

YZLN-2-RH



Actual product appearance may vary.

Prewired Enclosed Switches Series BZLN: Top Roller Arm Actuator; SPNO; No. 14 wire leads with 1/2 in - 14NPSM conduit hub; Right-hand Actuator

Product Specifications

Availability	Global
Operating Force (OF)	13,3 N [3 lb] max.
Release Force	1,11 N [0.25 lb] min.
Pretravel (PT)	1,98 mm [0.078 in] max.
Overtravel (OT)	11,91 mm [0.469 in] min.
Differential Travel (DT)	0,36 mm [0.014 in] max.
Product Type	Enclosed Sw itches
Actuator	Top Roller Arm
Lever Type	Roller - Adjustable
Circuitry	SPNO
Ampere Rating	15 A Ind./0.5 A Res./0.25 A Res.
Supply Voltage	125 Vac, 250 Vac, 480 Vac/125 Vdc/250 Vdc
Housing Material	Zinc Die-Cast
Termination Type	Preleaded w ith 1/2 in - 14NPSM Conduit
Series Name	LN
Sealing	NEMA 1, 3, 4, 13
UL File #	E12252
Operating Temperature	-32 °C to 71 °C [-25 °F to 160 °F]
Comment	Roller arm field adjustable 260 #&176 vertically; Right-hand Actuator; 3 Conductor 10-ft rubber cord w ith seal nut
Agency Approvals and Standards	UL, CSA
UNSPSC Code	39122213
UNSPSC Commodity	39122213 Limit Sw itches
Sealed	Industrial