1-1718492-6 ✔ ACTIVE


AMP | AMP MCP 1.5K, AMP MCP Connector System



TE Internal #: 1-1718492-6

12 V / 24 V, 36 Position, Automotive Housing for Male Terminals, Wire-to-Wire, 4 mm [.157 in] Centerline, Orange, Wire & Cable, Power, Hybrid

View on TE.com >

Automotive Parts > Automotive Connectors > Automotive Housings > AMP Unsealed Connector Housing

Nominal Voltage Architecture: **12 V, 24 V**

Connector & Housing Type: **Housing for Male Terminals**

Number of Positions: **36**

Sealable: **No**

Operating Temperature Range: **-40 – 120 °C [-40 – 248 °F]**

All AMP Unsealed Connector Housing (109)

Features

Product Type Features

Mixed & Hybrid Connector	Yes
Connector Shape	Rectangular
Connector & Housing Type	Housing for Male Terminals
Sealable	No
Primary Locking Feature	Integrated in Housing
Connector System	Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	36
Number of Rows	4

Electrical Characteristics

Operating Voltage	36 VDC

Nominal Voltage Architecture	12 V, 24 V

Body Features

Cable Exit Angle	180 °
Primary Product Color	Orange
Connector & Keying Code	F

Contact Features

Contact Size	1.6mm
Contact Type	Tab
Mating Tab Width	1.6 mm[.063 in]

Mechanical Attachment

Strain Relief	Without
Terminal Position Assurance	No
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT GF
Centerline (Pitch)	4 mm[.157 in]

Dimensions

Row-to-Row Spacing	4.2 mm, 10.9 mm[.165 in][.43 in]

Usage Conditions

Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]
Operating Temperature (Max)	120 °C[248 °F]

Operation/Application

Circuit Application	Power

Industry Standards

UL Flammability Rating	UL 94HB

Packaging Features

Packaging Method	Box
Packaging Quantity	330

Other

Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 1-1718485-6
CARRIER FOR RECEPT. INSERTS 36 POS




TE Part # CAT-T4827-T273
TIMER, RECEPTACLE AND TAB



TE Part # 2377783-4
36POS,AMP MCP 1.5K,TAB HSG ASSY, UNSLD

Also in the Series | AMP MCP Connector System

12 V / 24 V, 36 Position, Automotive Housing for Male Terminals, Wire-to-Wire, 4 mm [.157 in] Centerline, Orange, Wire & Cable, Power, Hybrid



Automotive Connector Locks & Position Assurance(1)




Automotive Housings(59)



Automotive Seals & Cavity Plugs(6)



Automotive Signal & Power Connector Housings(42)




Other Automotive Connector Accessories(4)


Also in the Series | AMP MCP 1.5K



Automotive Connector Caps & Covers (3)



Automotive Connector Locks & Position Assurance(1)



Automotive Housings(59)




Automotive Signal & Power Connector Housings(42)

Customers Also Bought

TE Part #6-967629-1
TAB HOUSING, 2.8MM, 18POS.



TE Part #9-968970-2
MCP2,8 GEH ASSY 6P



TE Part #1241846-1
TAB A 1.6x0.6 CONTACT CS SRC Sn



TE Part #4-1564412-1
18POS,TAB 1.6X0.6,TAB HSG,ASSY



TE Part #1-1718484-3
CARRIER FOR RECEPTACLE INSERTS


TE Part #188522-3
O-RING 25,07X2,62




TE Part #734767-1
DIE SET (CI-2)



TE Part #734790-1
SERVICE TOOL



TE Part #9-964598-1
HALTER F.9P RELAIS



TE Part #1355901-1
MCP9,5 BU-GEH 1P

Documents

Product Drawings

1.5MM TAB HSG 36 POS ASSY

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1718492-6_D.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-1718492-6_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1718492-6_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Application Specification

German