




Automotive Parts > Automotive Connectors > Automotive Headers > High Pin Count Header



PCB Mount Orientation: **Horizontal**
Termination Method to PCB: **Through Hole - Solder**
Sealable: **No**
Centerline (Pitch): **2.2 mm, 4 mm** [.087 in, .157 in]
Connector System: **Wire-to-Board**

[All High Pin Count Header \(43\)](#)

Features

Product Type Features

Connector Product Type	Connector Assembly
Mixed & Hybrid Header	Yes
Header Type	Fully Shrouded
Connector Shape	Rectangular
Sealable	No
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Signal Positions	80
Number of Sections	3
PCB Mount Orientation	Horizontal
Number of Positions	80
Number of Rows	3



Electrical Characteristics

Operating Voltage	12 VDC
Voltage Rating (Max)	12 VDC
Nominal Voltage Architecture	12 V

Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Mating Tab Width	.64 mm, 2.3 mm[.025 in][.091 in]
Mating Tab Thickness	.64 mm[.025 in]
Contact Type	Tab
Contact Mating Area Plating Material	Tin (Sn)

Termination Features

Termination Method to PCB	Through Hole - Solder
---------------------------	-----------------------

Mechanical Attachment

Panel Mount Feature	Without
Mating Retention Type	Locking Interface
PCB Mount Retention	Without
Mounting Holes	With
Mating Alignment	With
PCB Mount Alignment	Without

Housing Features

Centerline (Pitch)	2.2 mm, 4 mm[.087 in][.157 in]
--------------------	--------------------------------

Dimensions

Connector Width	87.2 mm[3.433 in]
PCB Thickness (Recommended)	1.6 mm[.063 in]
Connector Length	33.4 mm[1.315 in]
Profile Height from PCB	20.6 mm[.811 in]

Usage Conditions

Operating Temperature (Max)	65 °C, 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C[212 °F]
Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]

Operation/Application



Shielded	No
Circuit Application	Signal

Industry Standards

UL Flammability Rating	No
------------------------	----

Packaging Features

Packaging Quantity	6
Packaging Method	Tube

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 240°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # CAT-T319-CH8172
TH/.025 CONNECTOR SYSTEM,
HOUSING

Also in the Series | 0.64/025 Connector System

Automotive Connector Locks & Position Assurance(1)

Automotive Housings(174)

Automotive Seals & Cavity Plugs(2)

Other Automotive Connector Accessories(4)

Customers Also Bought

TE Part #DRC13-40PA
HDR, 40P, BLK, RA, 1032 FLG, SN/NI
/CU, A

TE Part #342368-1
187 FASTON,REC.,30-24 AWG,BR

TE Part #1571563-9
FSM8JSMATR=TACT,SMT,T&R

TE Part #1614911-6
CPF0805 25K 0.1% 25PPM 1K RL

TE Part #9-1879022-1
SMF3 470R 1%

TE Part #4-2176331-9
CRGP 2512 100K 1%

TE Part #6437288-3
SUPER SEAL 60POS CAP ASSY H AU

TE Part #174047-1
040 MLC PLUG HSG 20P NATURAL

TE Part #1565221-2
025/187 24POS 20CKT CAP ASSY H

TE Part #174046-1
040 MLC PLUG HSG 16P NATURAL



Documents

Product Drawings
025/090 80POS CAP ASSY

English

CAD Files
Customer View Model
ENG_CVM_CVM_1318751-7_J1.3d_stp.zip

English

3D PDF

3D

Customer View Model
ENG_CVM_CVM_1318751-7_J1.2d_dxf.zip

English

Customer View Model
ENG_CVM_CVM_1318751-7_J1.3d_igs.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications
Crimping of 025 Receptacle Contact

Japanese

Application Specification

Japanese

Instruction Sheets
025/090II I/O Connector

Japanese

Instruction Sheet (non U.S.)

Japanese

025/090II I/O Connector

Japanese

Instruction Sheet (non U.S.)

Japanese