



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Header**

Connector System: **Board-to-Board**

Number of Positions: **50**

Number of Rows: **2**

Centerline (Pitch): **1.27 mm [.05 in]**

Features

Product Type Features

Connector Shape	Rectangular
PCB Connector Type	PCB Mount Header
Connector System	Board-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Number of Columns	25
Number of Loaded Positions	50
Connector Contact Load Condition	Fully Loaded
Stackable	No
Number of Positions	50
Number of Rows	2



PCB Mount Orientation	Right Angle
Board-to-Board Configuration	Co-Planar, Orthogonal

Body Features

Connector Profile	Standard
Primary Product Color	Black

Contact Features

PCB Contact Termination Area Plating Material Thickness	4 – 6 µm[157.48 – 236.22 µin]
Contact Shape & Form	Rectangular
Contact Layout	Matrix
Contact Mating Area Length	4 mm[.157 in]
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold (Au)
Contact Type	Pin
Contact Current Rating (Max)	1.1 A
PCB Contact Termination Area Plating Material	Tin

Termination Features

Termination Method to PCB	Surface Mount
---------------------------	---------------

Mechanical Attachment

Mounting Alignment Feature Length	.75 mm[.029 in]
PCB Mount Retention Type	Location Peg
PCB Mount Alignment Type	Locating Posts
Mating Alignment Type	Polarization
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	With
PCB Mount Retention	With

Housing Features

Mating Entry Location	Side
Centerline (Pitch)	1.27 mm[.05 in]
Housing Material	Liquid Crystal Polymer (LCP)

Dimensions

Connector Width	10 mm[.394 in]
-----------------	----------------



Connector Height	4.25 mm[.167 in]
Connector Length	36.83 mm[1.45 in]
Profile Height from PCB	4.25 mm[.167 in]
Row-to-Row Spacing	1.27 mm[.05 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

Operation/Application

Shielded	No
Circuit Application	Power & Signal

Industry Standards

Compatible With Agency/Standards Products	DIN, UL
Industry Standard	IEC
Compatible With Approved Standards Products	UL
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Reel Diameter	330 mm[12.99 in]
Packaging Quantity	560
Packaging Method	Tape & Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>







EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: FEB 2026 (253) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 154719-E SMCB 50 F AB VV 7-03 CL * H007 137 E002	 TE Part # 173794-E IDCCS SMC 1,27 50 * AU AUI 200 PVC	 TE Part # 154742-E SMCQ 50 F AB VV 7-03 CL * 0007 137 E002	 TE Part # 234199-E SMCB 50 F AB VV 7-23 CL * H007 137 E002
 TE Part # 394394-E SMCB 50 F AB VV 7-13 CL * HE07 137 E002	 TE Part # 474968-E SMCQ 48 F AB 0517 7-03 CL * 0007 137 E00	 TE Part # 534157-E SMCB 36 F AB 0546 7-23 CL * H007 137 E00	 TE Part # 223727-E SMCQ 40 F AB 0418 7-03 CL * 0007 137 E00
 TE Part # 474357-E SMCB 50 F AB VV 6-01 VHSL * 0008 137 E00	 TE Part # 124045-E SMCB 50 F AB VV 6-03 CLHD * H007 137 E00	 TE Part # 223729-E SMCB 40 F AB 0418 7-03 CL * H007 137 E00	 TE Part # 173795-E IDCCS SMC 1,27 50 * AU AUI 300 PVC



TE Part # 154807-E
SMCB 50 F AB VV 7-13 CL * H007 137 E002




TE Part # 214347-E
SMCB 50 F AB VV 6-01 VH * 0008 137 E002



TE Part # 454766-E
SMCB 50 F AB VV 7-03 CL * H007 137 E002



TE Part # 024403-E
SMCB 50 F AB VV 3-01 * * 0008 137 POS 05



TE Part # 173793-E
IDCCS SMC 1,27 50 * AU AUI 100 PVC



TE Part # 394396-E
SMCQ 50 F AB VV 7-03 CL * HE07 137 E002




TE Part # 524657-E
SMCB 50 F AB VV 6-01 VHSL * 0008 137 E00

Also in the Series | ERNI SMC



Board-In Connectors(6)




Board-to-Board Headers & Receptacles(79)



Connector Adapters & Connector Savers(41)




High Speed I/O Cable Assemblies(27)



PCB Headers & Receptacles(79)




Rectangular Power Connectors(84)




Wire-to-Board Headers & Receptacles (3)

Customers Also Bought



TE Part #354181-E
MSPEED 50 F SMDTHR F10 B AB VV 137 094 *



TE Part #244838-E
SMCQ 50 M AB VV 8-13 CL * H007 137 E005



TE Part #T2580032154-000
PIN-Q2-F



TE Part #464689-E
DRCQ 2,54 20 M * SMD * 137 E012 168 GU-H






TE Part #T2040064201-000
HE-006-FC



TE Part #T1930060000-000
H6BPR-AG



TE Part #234479-E
SRCP 1,27 12 F 1 I2426 137 E1 162 1,07
T



TE Part #294920-E
SRCP 1,27 12 M 1 SMD 137 E1 094 *
GU-H *



TE Part #374338-E
DRCBUG B 2,54 20 * CSI 165 E012
ADV J 2



TE Part #1-825437-2
MOD 2 PINHDR 1X12P.

Documents

Product Drawings

SMCB 50 M AB VV 7-03 CL * 0007 137 E004

German

CAD Files

Customer View Model

ENG_CVM_CVM_154765-E_1.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_154765-E_1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_154765-E_1.3d_igs.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Datasheet - ERNI SMC 1.27mm Connectors

English

Product Specifications

Product Specification

English

Product Specification

English

154765-E

PCB Mount Header, Right Angle, Board-to-Board, 50 Position, 1.27 mm [.05 in]
Centerline, Fully Shrouded, Gold (Au), Surface Mount, ERNI SMC

