170092-2 ✔ ACTIVE


FASTIN-FASTON | FASTIN-FASTON 250



TE Internal #: 170092-2

Quick Disconnect Receptacle, Uninsulated, 18 – 14 AWG, .82 – 2.08 mm² Wire, 6.35 mm [.25 in] Tab Width, F-Crimp, Straight, FASTIN-FASTON 250

View on TE.com >

Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.82 – 2.08 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.7 mm [.027 in]**

Features

Product Type Features

Insertion Force	Normal

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.7 mm[.027 in]
Terminal Orientation	Straight
Contact Base Material	Phosphor Bronze
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable

Mechanical Attachment

Locking Lance Height	1.2 mm[.047 in]
Wire Insulation Support	With
Mating Retention Type	Locking Lance

Dimensions

Product Length	19.1 mm[.75 in]
Compatible Insulation Diameter Range	3.1 – 4.1 mm[.12 – .16 in]
Terminal Material Thickness	.33 mm[.013 in]
Wire Size	.82 – 2.08 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Packaging Features

Packaging Quantity	4000
Packaging Method	Strip/Reel

Other

Line	FASTON .250

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 2150238-1
OCEAN_2.0_Applicator-E-110F180F-REM



TE Part # 7-2150238-7
OCEAN_2.0_SPARE_PART_KIT-110F180F




TE Part # 2150238-2
OCEAN_2.0_Applicator-E-110F180F-REA



TE Part # 720725-1
DAHT 250 FASTIN-ON TAB REC 18-14 ASSY

Also in the Series | FASTIN-FASTON 250



Crimp Terminal Housings(192)



Insertion & Extraction Tools(2)



Quick Disconnects(217)


Customers Also Bought



TE Part #172501-1
MIC MARK-2 PLUG HSG 21P



TE Part #178964-8
DYNAMIC D-3 W-T-W TAB HSG 20P




TE Part #2-292262-8
DBL ROW (H) DIP TYPE WITH BOAR




TE Part #353717-2
DYNAMIC D-3 REC CONT. 3L AU 0.38 L/P



TE Part #1939556-4
AMP SEAL16 2P CAP ASSY WITH RESIST 120



TE Part #2354263-1
V23074A2002A403-SZ-CBOX




TE Part #175567-1
HYBRID I/O CONN PLUG HSG 26P



TE Part #172191-1
ECONOSEAL-J CONN PLUG 8P



TE Part #1897646-2
LEVER HSG FOR CPA



TE Part #1393458-1
V23540M1000Z111=DICHTTULLE ELO

Documents

Product Drawings

FF 250 REC 18-14AWG TPPB REREELING

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_170092-2_R.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_170092-2_R.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_170092-2_R.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (non U.S.)

Japanese

Instruction Sheet (non U.S.)

Japanese