170234-2 ✔ ACTIVE


Positive Lock | Positive Lock 250

TE Internal #: 170234-2

Quick Disconnect Receptacle, Uninsulated, 12 – 10 AWG, 3.31 – 5.26 mm² Wire, 6.35 mm [.25 in] Tab Width, F-Crimp, Straight, Brass, Positive Lock 250

View on TE.com >

Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **3.31 – 5.26 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Low

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Product Length	22.1 mm[.87 in]
Compatible Insulation Diameter Range	3.81 – 5.08 mm[.15 – .2 in]
Terminal Material Thickness	.41 mm[.016 in]
Wire Size	3.31 – 5.26 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	UL

Packaging Features

Packaging Quantity	1500
Packaging Method	Strip/Reel

Product Compliance


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 171809-2
POSITIVE LOCK (PL) HOUSING




TE Part # 7-2151724-7
OCEAN_2.0_SPARE_PART_KIT-140F220F



TE Part # 2305570-1
Strip Terminal Cutter-Side Feed-No Crimp




TE Part # 2151724-2
OCEAN_2.0_Applicator-S-140F220F-RSA



TE Part # 171809-1
POSITIVE LOCK (PL) HOUSING

Also in the Series | Positive Lock 250



Automotive Terminals(1)



Crimp Terminal Housings(176)



Insertion & Extraction Tools(3)




Insulation Boots & Sleeves(5)




Quick Disconnects(171)

Customers Also Bought


TE Part #170354-1
LOW PROFILE E.I. CONNECTOR




TE Part #171404-1
ELECTRO TAP 14-16




TE Part #171809-2
POSITIVE LOCK (PL) HOUSING




TE Part #172864-1
250 POSITIVE DBL LOCK 2P NATUR




TE Part #329860
TERMINAL,TERMI-FOIL 16-14




TE Part #368523-1
E-S MK-2(+) 3P PLUG ASS'Y




TE Part #626541-1
4 WAY FASTIN-ON HSG TAB NATURAL PA.66



TE Part #880110
FASTON HOUSING RECEPTACLE NAT NYLON



TE Part #880310-1
2 WAY FF 250 HOUSING TAB NYLON 6.6 NAT



TE Part #925713-1
M-N-L PIN TPBR

Documents

Product Drawings

PL 250 REC 12-10 AWG 0.406 X 42.3

Japanese

CAD Files

Customer View Model

ENG_CVM_CVM_170234-2_K.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_170234-2_K.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_170234-2_K.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

Crimping of Positive Lock Receptacle Contact

English

Application Specification

English

Agency Approvals

UL

English