




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **509 – 1900 CMA**

Mating Tab Width: **6.35 mm [ .25 in ]**

Features

Product Type Features

|                 |        |
|-----------------|--------|
| Insertion Force | Normal |
|-----------------|--------|

Configuration Features

|                     |        |
|---------------------|--------|
| Connection Capacity | Single |
|---------------------|--------|

Electrical Characteristics

|                |       |
|----------------|-------|
| Voltage Rating | 300 V |
|----------------|-------|

Body Features

|                     |       |
|---------------------|-------|
| Insulation Material | Nylon |
|---------------------|-------|

Contact Features

|                                |                   |
|--------------------------------|-------------------|
| Quick Disconnect Terminal Type | Receptacle        |
| Mating Tab Width               | 6.35 mm[.25 in]   |
| Mating Tab Thickness           | .81 mm[.032 in]   |
| Terminal Orientation           | Straight          |
| Contact Base Material          | Phosphor Bronze   |
| Terminal Plating Material      | Tin               |
| Crimp Type                     | Compression Crimp |
| Barrel Type                    | Closed            |

Termination Features

|                       |              |
|-----------------------|--------------|
| Product Terminates To | Wire & Cable |
|-----------------------|--------------|

Mechanical Attachment

|                         |      |
|-------------------------|------|
| Wire Insulation Support | With |
|-------------------------|------|



|                       |        |
|-----------------------|--------|
| Mating Retention Type | Dimple |
|-----------------------|--------|

Dimensions

|                                      |                  |
|--------------------------------------|------------------|
| Product Length                       | 20.2 mm[.795 in] |
| Compatible Insulation Diameter Range | 3.3 mm[.13 in]   |
| Wire Size                            | 509 – 1900 CMA   |

Usage Conditions

|                   |                     |
|-------------------|---------------------|
| Insulation Option | Partially Insulated |
|-------------------|---------------------|

Packaging Features

|                    |             |
|--------------------|-------------|
| Packaging Quantity | 500         |
| Packaging Method   | Loose Piece |

Other

|              |     |
|--------------|-----|
| Barrel Color | Red |
|--------------|-----|

Product Compliance

For compliance documentation, visit the product page on TE.com>



|                                               |                                                                                                                                |
|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                      |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                      |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                        |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2025 (250)<br>Candidate List Declared Against: JUN 2020 (209)<br>Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                               |
| Solder Process Capability                     | Not applicable for solder process capability                                                                                   |

Product Compliance Disclaimer









This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>





Also in the Series | FASTON 250

|                                                                                                                    |                                                                                                                        |                                                                                                                               |                                                                                                                     |
|--------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
|  <p>Compression Connectors(4)</p> |  <p>Crimp Terminal Housings(115)</p> |  <p>Insulation Boots &amp; Sleeves(16)</p> |  <p>Magnet Wire Terminals(1)</p> |
|  <p>PCB Terminals(133)</p>       |  <p>Quick Disconnects(417)</p>      |  <p>Splices(4)</p>                        |                                                                                                                     |

Customers Also Bought

|                                                                                                                                    |                                                                                                                                     |                                                                                                                                      |                                                                                                                                      |
|------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
|  <p>TE Part #CC2628-000<br/>B-106-3631CS100</p> |  <p>TE Part #CC2644-000<br/>B-106-8502CS100</p> |  <p>TE Part #CC2631-000<br/>B-106-7401CS100</p> |  <p>TE Part #CC2637-000<br/>B-106-1802CS100</p> |
|  <p>TE Part #CC2643-000<br/>B-106-7502CS100</p> |  <p>TE Part #CC2649-000<br/>B-106-1803CS50</p>  |  <p>TE Part #CC2621-000<br/>B-106-1501CS100</p> |  <p>TE Part #CC2641-000<br/>B-106-3632CS100</p> |



Documents

CAD Files

Customer View Model

ENG\_CVM\_CVM\_170603-2\_E.2d\_dxf.zip

English

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_170603-2\_E.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_170603-2\_E.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English