




Part Number : [1712242013](#)
Product Description : zSFP+ Stacked Ganged Assembly with Metal Spring Fingers, 2-by-2 with Outer Down/Up Light Pipes, 80 Circuits
Series Number : 171224
Status : Active
Product Category : High-Speed I/O Connectors



Documents and Resources

Drawings

[1712242013_sd.pdf](#)
[PK-170071-002-001.pdf](#)

3D Models and Design Files

[STEP AP242](#)
[SOLIDWORKS](#)
[Creo](#)
[EE-170071-0001-001.pdf](#)
[SP-170426-1000-001.zip](#)

Specifications

[AS-170071-0002-001.pdf](#)
[PS-170071-0001-001.pdf](#)
[TS-170071-0001-001.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant with Exemption 44; 34; 33
China RoHS	 per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2025)6375-

	DC (05 Nov 2025)
EU RoHS	Compliant per EU 2015/863

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

Part Details

General

Status	Active
Category	High-Speed I/O Connectors
Series	171224
Description	zSFP+ Stacked Ganged Assembly with Metal Spring Fingers, 2-by-2 with Outer Down/Up Light Pipes, 80 Circuits
Application	Module-to-Board
Component Type	Receptacle
Product Name	zSFP Plus,zSFP+
Type	Pluggable
UPC	884982823594

Agency

UL	E29179
----	--------

Electrical

Current - Maximum per Contact	0.5A
Data Rate	28.0 Gbps
Shielded	Yes
Shield Type	EMI Fingers
Voltage - Maximum	30V AC (RMS)/DC

Physical

Circuits (Loaded)	80
Color - Resin	Black
Durability (mating cycles max)	100
Flammability	94V-0
Gender	Female
Lock to Mating Part	Yes
Material - Metal	High Performance Alloy (HPA)
Material - Plating Mating	Gold
Material - Plating Termination	Matte Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	49.848/g
Number of Rows	2
Orientation	Right Angle
Packaging Type	Tray
Panel Mount	No
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	1.57mm
Pitch - Mating Interface	0.80mm
Pitch - Termination Interface	0.80mm
Plating min - Mating	0.762µm
Plating min - Termination	0.762µm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Ports	4
Temperature Range - Operating	-40° to +85°C
Termination Interface Style	Through Hole - Compliant Pin

Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----