**Part Number :** 191600039
**Product Description :** Twist Lock Splice for 22-14 AWG Wire, Grey, Carton
**Series Number :** 19160
**Status :** Active
**Product Category :** Splices
**Engineering Part Number :** TL-G



## Documents and Resources

### Drawings

191600039_sd.pdf

### Specifications

PS-19902-013-001.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2025)4165-DC (25 June 2025) |
| EU RoHS | Compliant per EU 2015/863 |

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

## Part Details

### General

| | |
|---|---|
| Status | Active |
| Category | Splices |
| Series | 19160 |
| Description | Twist Lock Splice for 22-14 AWG Wire, Grey, Carton |
| Product Name | Closed-End Twist Lock |
| Style | Twist Lock |
| Type | Closed-end Connector |
| UPC | 800753110434 |

### Agency

| | |
|---|---|
| CSA | LR700095 |
| UL | E32244 |

### Electrical

| | |
|---|---|
| Voltage - Maximum | 300V |

### Physical

| | |
|---|---|
| Barrel Type | Closed |
| Color - Resin | Gray |
| Flammability | 94V-2 |
| Insulation | Nylon (PA) |
| Material - Metal | Copper |
| Material - Plating Mating | Tin |
| Material - Plating Termination | Tin |
| Net Weight | 0.431/g |
| Packaging Type | Carton |
| Temperature Range - Operating | 105°C |

| | |
|---|---|
| Wire Insulation Diameter | 6.60mm max. |
| Wire Size (AWG) | 14, 16, 18, 20, 22 |