





Introducing  
**MULTIGIG RT 2-R**  
Ruggedized Connectors  
for VPX Applications



## PART CONFIGURATIONS



### DAUGHTERCARD

| Module Position        |              | Part No.                                             |                                                                 |
|------------------------|--------------|------------------------------------------------------|-----------------------------------------------------------------|
|                        |              | MULTIGIG RT 2 Connectors                             | Ruggedized MULTIGIG RT 2-R (Extended Pad Wafers)                |
| PO                     |              | 1410189-3                                            | 2102772-1                                                       |
| P1, P2, P3, P4, P5, P6 | Differential | 1410187-3                                            | 2102771-1                                                       |
|                        | Single-Ended | 1410190-3                                            | 2102847-1                                                       |
| Keying Guide Modules   |              | 1-1469492-X<br>Standard (Zinc Die Cast) Guide Socket | 2000713-X<br>Machined 6061 Aluminum Guide Socket, w/ESD Contact |

See TE drawings for guide module and pin options.


### BACKPLANE

| Module Position  |  | Part No.                                          |                                                      |
|------------------|--|---------------------------------------------------|------------------------------------------------------|
|                  |  | MULTIGIG RT 2 Connectors                          | Ruggedized MULTIGIG RT 2-R (Quad Redundant Contacts) |
| JO               |  | 1410186-1                                         | 2102735-1                                            |
| J1, J3, J4, J5   |  | 1410140-1                                         | 2102736-1                                            |
| J2, J6           |  | 1410142-1                                         | 2102737-1                                            |
| Keying Guide Pin |  | 1-1469491-X<br>Standard (Zinc Die Cast) Guide Pin | 2000676-X<br>Stainless Steel Guide Pin               |

See TE drawings for guide module and pin options.

# MULTIGIG RT 2-R Connectors

## PART CONFIGURATIONS



### REAR TRANSITION MODULE

|                      |                             | Part No.                                             |                                                                 |
|----------------------|-----------------------------|------------------------------------------------------|-----------------------------------------------------------------|
| Module Position      |                             | MULTIGIG RT 2 Connectors                             | Ruggedized MULTIGIG RT 2-R (Extended Pad Wafers)                |
| RPO                  |                             | 1410968-3                                            | 2102773-1                                                       |
| RP1                  | Differential                | 1410975-3                                            | 2102774-1                                                       |
|                      | Differential & Single-Ended | 1410970-3                                            | 2102849-1                                                       |
| RP2                  | Differential                | 1410971-3                                            | 2102775-1                                                       |
|                      | Single-Ended                | 1410972-3                                            | 2102848-1                                                       |
| RP3, RP4, RP5, RP6   | Differential                | 1410975-3                                            | 2102774-1                                                       |
|                      | Single-Ended                | 1410190-3                                            | 2102847-1                                                       |
| Keying Guide Modules |                             | 1-1469492-X<br>Standard (Zinc Die Cast) Guide Socket | 2000713-X<br>Machined 6061 Aluminum Guide Socket, w/ESD Contact |

### REAR TRANSITION BACKPLANE


|                  |            | Part No.                                        |                                                      |
|------------------|------------|-------------------------------------------------|------------------------------------------------------|
| Module Position  |            | MULTIGIG RT 2 Connectors                        | Ruggedized MULTIGIG RT 2-R (Quad Redundant Contacts) |
| RJO              | See Note 1 | 1410964-1                                       | 2102768-1                                            |
|                  | See Note 2 | 1410965-1                                       | 2102850-1                                            |
| RJ1              | See Note 3 | 1410140-1                                       | 2102736-1                                            |
|                  | See Note 4 | 1410966-1                                       | 2102851-1                                            |
| RJ2              |            | 1410186-1                                       | 2102735-1                                            |
| RJ3              |            | 1410142-1                                       | 2102737-1                                            |
| RJ4, RJ5, RJ6    |            | 1410140-1                                       | 2102736-1                                            |
| Keying Guide Pin |            | 1410956-1<br>Standard (Zinc Die Cast) Guide Pin | 2226127-1<br>Stainless Steel Guide Pin               |

#### Notes (Reference VITA 46.10; Observation 3-6):

- Note 1: 16 column shell, 15 columns of contacts
- Note 2: 16 column shell, 7 columns of contacts present (plus contacts i9-16)
- Note 3: 16 column shell, 16 columns of contacts
- Note 4: 16 column shell, 8 columns of contacts present (plus contacts ii-8)

See TE drawings for guide module and pin options.

## ASSOCIATED VPX SOLUTIONS




### MEZALOK Mezzanine Connectors (Compliant to VITA 61)

- Utilizes the proven, reliable MIL-55302 Mini-Box contact interface, with four points of contact
- Backwards compatible with XMC board footprint
- Accommodates 10mm, 12mm, 15mm and 18mm stack heights
- Solder ball SMT attach in SnPb and RoHS options
- 114 (6 x 19) positions and 60 (6 x 10) positions
- Protected “stub-proof” socket contacts w/superior signal integrity
- Exceptional solder joint reliability (1000+ cycles thermal shock)




### MULTI-BEAM XLE Power Connectors (Compliant to VITA 62)

- 20A and 50A power contacts, plus signal contacts
- 3-beam high-conductivity-copper contact design allows for a greater angular misalignment between mating connectors and offers a lower mating force
- Slim guide sockets reduce the overall PCB footprint
- Vented housing allows for better heat dissipation
- Hot-plug capable



### Optic Connectors (Compliant to VITA 66)

- Light weight
- High bandwidth
- EMI immunity
- 3 fiber optic interface types available:
  - 66.1 has two MT ribbon ferrules up to 24 fibers each
  - 66.2 four ARINC 801 termini
  - 66.3 one expanded beam lensed insert with four fibers



### RF Modules (Compliant to VITA 67)

- Excellent channel-to-channel isolation and RF performance to 65 GHz
- Modular design permits application specific configuration with high RF contact count
- Float mounted jack maintains positive RF ground
- .240 center-to-center spacing
- 4 and 8 position modules are designed to meet the requirements of VITA 67.1 and VITA 67.2

# MULTIGIG RT 2-R Connectors



## KEY FEATURES

Quad-redundant contact system supports high levels of shock/vibration

Compliant to VITA 46 for Open VPX applications

Supports Ethernet, Fibre Channel, InfiniBand applications, PCIe and Serial RapidIO high speed protocols

Modular, lightweight connector system

Robust “pinless” interface

Differential, single-ended and power

Ruggedized guide hardware available

Supports 0.8 inch card slot pitches

VITA 46 compliance enables upgrade in existing VPX applications

Can be combined with high power modules (VITA 62), RF modules (VITA 67) and Optical modules (VITA 66)

## DESCRIPTION

TE's MULTIGIG RT 2-R ruggedized, light weight, high speed board-to-board interconnect is compliant to VITA 46 standard. This connector system features the modularity and flexibility of the MULTIGIG RT 2 connector, with a new quad-redundant contact structure designed for high vibration levels.

## APPLICATIONS

Rugged embedded computing applications:

- Ground Defense
- Missile Defense
- Electronic Systems / C4ISR
- Space
- Commercial and Military Aerospace

## MATERIALS

Contacts: High performance copper alloy, plated 50 µin Au over 50 µin Ni in mating area, tin-lead on compliant pin tails

Housings: High temperature thermoplastic

Rugged Guide Hardware: Aluminum or passivated stainless steel

## MECHANICAL

Operating Temperature: -55 to +105°C

Mating Force: 0.75 N [2.70 ozf] maximum per contact, same as standard MULTIGIG RT 2 backplane connector

## STANDARDS & SPECIFICATIONS

Compliant to VITA 46 (VPX)

Product Specification: 108-2072

Application Specification: 114-13056

Qualification Test Report: 501-544

## PHYSICAL OR OTHER PROPERTIES

Tested to HALT (Highly accelerated life test) vibration levels (0.2G<sup>2</sup>/Hz) per VITA 72

Connector modules available for 3U and 6U VPX slot profiles, including rear transition modules

Reliable press-fit termination, requiring only flat rock tooling

Lightest weight VPX connector system: mated set of connectors and guide hardware for typical module and backplane slots:  
3U - 62.66g (2.21 oz); 6U - 140.26g (4.95 oz)

## FOR MORE INFORMATION

### Technical Support

Internet: [www.te.com/ADM](http://www.te.com/ADM)

|                      |                   |
|----------------------|-------------------|
| <b>Americas:</b>     | +1 800 522-6752   |
| <b>Asia Pacific:</b> | +86 400 820 6015  |
| <b>Europe:</b>       |                   |
| Austria:             | +43 1 905 601 228 |
| Baltic Regions:      | +46 8 5072 5000   |
| Benelux:             | +31 73 6246 999   |
| France:              | +33 1 34 20 86 86 |
| Germany:             | +49 6251-133 1999 |
| Italy:               | +39 011-401 2632  |
| Nordic:              | +46 8 5072 5000   |
| Spain/Portugal:      | +34 93-2910366    |
| Switzerland:         | +41 52 633 66 26  |
| United Kingdom:      | +44 800 267 666   |
| Czech Republic:      | +420 800 701 462  |
| Poland:              | +48 800 702 309   |
| Hungary:             | +36 809 874 04    |
| Russia:              | +7495 790 790 2   |

Follow us on Twitter for all the latest product news  
@TEConnectivity, and on Facebook, TEConnectivity.

[www.te.com/ADM](http://www.te.com/ADM)

© 2013 Tyco Electronics Corporation. All Rights Reserved.

1773466-4 ADM/RRD 2.5M 01/2013

MEZALOK, MULTI-BEAM XL, MULTIGIG RT, TE Connectivity and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies.

Other products, logos, and company names mentioned herein may be trademarks of their respective owners. InfiniBand is a trademark of the InfiniBand Trade Association.

While TE has made every reasonable effort to ensure the accuracy of the information herein, nothing herein constitutes any guarantee that such information is error-free, or any other representation, warranty or guarantee that the information is accurate, correct, reliable current. The TE entity issuing this publication reserves the right to make any adjustments to the information contained herein at any time without notice. All implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose are expressly disclaimed. The dimensions herein are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

