



Part Number : [2018431031](#)
Product Description : MultiCat High-Power Right-Angle Header, 3 Circuits, Key B, Gray
Series Number : 201843
Status : Active
Product Category : PCB Headers and Receptacles
Engineering Number : 2018431031-FCT



Documents & Resources

Drawings

[2018431031_sd.pdf](#)
[2018420000-PK-000.pdf](#)

3D Models and Design Files

[STEP AP242](#)
[SOLIDWORKS](#)
[Creo](#)
[Symbol and Footprint \(Multi-Format\)](#)
[SYM-201843-1030-001.zip](#)

Specifications

[2018400000-AS-000.pdf](#)
[2018400000-PS-000.pdf](#)
[2018400000-TS-000.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant with Exemption 3; 44; 33; 34
China RoHS	per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Contains Lead per D(2025)4165-DC (25 June 2025)

EU RoHS	Compliant with Exemption 6(c) per EU 2015/863
---------	---

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

Part Details

General

Status	Active
Category	PCB Headers and Receptacles
Series	201843
Description	MultiCat High-Power Right-Angle Header, 3 Circuits, Key B, Gray
Application	Power, Wire-to-Board
Component Type	PCB Header
Product Name	MultiCat
UPC	889056747684

Agency

UL	E29179
----	--------

Electrical

Current - Maximum per Contact	40.0A
Voltage - Maximum	1000V AC/DC

Physical

Breakaway	No
Circuits (Loaded)	3
Circuits (maximum)	3
Color - Resin	Gray
Durability (mating cycles max)	500
First Mate / Last Break	No
Flammability	94V-0
Glow-Wire Capable	No
Guide to Mating Part	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	PEI
Net Weight	11.086/g
Number of Rows	1
Orientation	Right Angle
Packaging Type	Tray
PCB Thickness - Recommended	2.50mm
Pitch - Mating Interface	7.40mm
Plating min - Mating	0.102µm
Plating min - Termination	5.080µm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Shrouded	Yes
Temperature Range - Operating	-40° to +150°C
Termination Interface Style	Through Hole

Mates With / Use With

Mates with Part(s)

Description	Part Number
MultiCat High-Power Inline	<u>201841</u>

Receptacle Housings	
---------------------	--

This document was generated on Sep 23, 2025