



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Header**

Connector System: **Cable-to-Board**

Number of Positions: **4**

Number of Rows: **1**

Centerline (Pitch): **1.27 mm [.05 in]**

Features

Product Type Features

Connector Shape	Rectangular
PCB Connector Type	PCB Mount Header
Connector System	Cable-to-Board
Header Type	Fully Shrouded
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Number of Columns	4
Number of Loaded Positions	4
Connector Contact Load Condition	Fully Loaded
Number of Positions	4
Number of Rows	1
PCB Mount Orientation	Right Angle

Electrical Characteristics



Insulation Resistance	10000 MΩ
Dielectric Withstanding Voltage (Max)	500 Vrms

Body Features

Primary Product Color	Black
-----------------------	-------

Contact Features

PCB Contact Termination Area Plating Material Thickness	4 – 6 μm[157.48 – 236.22 μin]
Contact Shape & Form	Rectangular
Contact Layout	Inline
Contact Mating Area Length	2.5 mm[.098 in]
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold (Au)
Contact Type	Pin
Contact Current Rating (Max)	4.3 A
PCB Contact Termination Area Plating Material	Tin

Termination Features

Termination Method to PCB	Surface Mount
---------------------------	---------------

Mechanical Attachment

Mating Retention Type	Friction Lock
Mounting Alignment Feature Length	.75 mm[.029 in]
Mating Retention	With
Mating Alignment Type	Polarization
PCB Mount Alignment Type	Pegs
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	With
PCB Mount Retention	Without

Housing Features

Mating Entry Location	Side
Centerline (Pitch)	1.27 mm[.05 in]
Housing Material	Liquid Crystal Polymer (LCP)

Dimensions

Connector Width	7.2 mm[.283 in]
-----------------	-----------------



Connector Height	2.98 mm[.117 in]
Profile Height from PCB	2.98 mm[.117 in]
Connector Length	10.16 mm[.4 in]

Usage Conditions

Operating Temperature (Max)	150 °C[302 °F]
Operating Temperature Range	-55 – 150 °C[-67 – 302 °F]

Operation/Application

Assembly Process Feature	Pick and Place Cover
Circuit Application	Power & Signal

Industry Standards

Compatible With Agency/Standards Products	DIN, UL
Industry Standard	IEC
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Reel Diameter	330 mm[12.99 in]
Packaging Quantity	1000
Packaging Method	Tape & Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: FEB 2026 (253) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 384528-E SRCP 1,27 4 F 1 IDC22 137 E1 162 1,27 TR	 TE Part # 214049-E SRCA 1,27 4 F 1 I2426 137 E1 094 1,07 TR	 TE Part # 374209-E SRCP 1,27 4 F 1 IDC22 137 E1 162 1,27 TR	 TE Part # 284730-E SRCA 1,27 4 F 1 I2426 137 E1 105 1,07 TR
 TE Part # 839018-E IDCCS SRC 1,27 4 * SFX SFX 300 PVC	 TE Part # 839057-E IDCCS SRC 1,27 4 * SFX SFX 300 HT	 TE Part # 839047-E IDCCS SRC 1,27 4 * SFX AFU 200 PVC	 TE Part # 839468-E IDCCS SRC 1,27 4 * SFX SFX 700 PVC
 TE Part # 839315-E IDCCS SRC 1,27 4 * SFX SFX 500 HT	 TE Part # 384975-E SRCP 1,27 4 F 1 SMD 137 * 105 * GURT RLV	 TE Part # 214025-E SRCP 1,27 4 F 1 I2426 137 * 162 1,07 TRA	 TE Part # 224394-E SRCP 1,27 4 F 1 I2426 137 * 162 1,07 TRA
 TE Part # 839016-E IDCCS SRC 1,27 4 * SFX SFX 100 PVC	 TE Part # 839017-E IDCCS SRC 1,27 4 * SFX SFX 200 PVC	 TE Part # 224398-E SRCA 1,27 4 F 1 I2426 137 E1 094 1,07 TR	 TE Part # 394895-E SRCA 1,27 4 F 1 IDC22 137 E1 094 1,27 TR



TE Part # 839104-E
IDCCS SRC 1,27 4 * SFX SFX 50 HT

TE Part # 364485-E
SRCP 1,27 4 F 1 SMD 137 * 094 * GURT RLV

TE Part # 394897-E
SRCA 1,27 4 F 1 IDC22 137 E1 094 1,27 TR

TE Part # 364484-E
SRCP 1,27 4 F 1 SMD 137 * 168 * GURT VLP

Also in the Series | ERNI MiniBridge

Board-to-Board Headers & Receptacles(1)

Connector Hardware(1)

PCB Headers & Receptacles(32)

Pluggable I/O Cable Assemblies(24)

Rectangular Power Connectors(48)

Standard Rectangular Connectors(16)

Customers Also Bought

TE Part #284697-E
SRCP 1,27 4 M 1 SMD 137 E1 094 * GU-H *

TE Part #354094-E
SMCB 16 M AB VV 7-03 CL * 0007 137 E004

TE Part #354081-E
SMCQ 40 F AB VV 7-03 CL * 0007 137 E002

TE Part #254539-E
SMCQ 40 M AB VV 8-03 CL * H007 137 E005

TE Part #203290-E
MJIM IM 1X1 S 88 GF5 X R THRU * L3A H3D0

TE Part #384845-E
SRCP 1,27 2 F 1 SMD 137 * 094 * GURT RLV

TE Part #364485-E
SRCP 1,27 4 F 1 SMD 137 * 094 * GURT RLV

TE Part #214014-E
SRCA 1,27 8 M 1 SMD 137 E1 094 * GURT *



TE Part #354055-E
SMCB 16 F AB VV 7-13 CL * H007 137
E002



TE Part #9-1393222-7
V23061B1005A501=MINISTARKSTROM

Documents

Product Drawings

SRCA 1,27 4 M 1 SMD 137 E1 094 * GURT *

German

CAD Files

Customer View Model

ENG_CVM_CVM_214012-E_1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_214012-E_1.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_214012-E_1.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Application Specification

English