**Part Number :** 2178511134
**Product Description :** Pre-Crimped Lead Perma-Seal-to-Pigtail, Solderless, Tin (Sn) Plating, 300.00mm Length, Blue
**Series Number :** 217851
**Status :** Active
**Product Category :** Power and Signal Cable Assemblies



## Documents & Resources

### Drawings

2178511134_sd.pdf

STEP AP242

SOLIDWORKS

Creo

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | per SJ/T 11365-2006 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)7663-DC (21 Jan 2025) |
| EU RoHS | Compliant per EU 2015/863 |

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest
- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

## Part Details

### General

| | |
|---|---|
| Status | Active |
| Category | Power and Signal Cable Assemblies |
| Series | 217851 |
| Description | Pre-Crimped Lead Perma-Seal-to-Pigtail, Solderless, Tin (Sn) Plating, 300.00mm Length, Blue |
| Assembly Configuration | Pre-crimped Lead Only |
| Connector to Connector | Perma-Seal-to-Pigtail |
| Product Name | Perma-Seal |
| UPC | 195842209930 |

### Electrical

| | |
|---|---|
| Current - Maximum per Contact | 20.0A |
| Voltage - Maximum | 600V |

### Physical

| | |
|---|---|
| Cable Length | 300.00mm |
| Circuits (Loaded) | 1 |
| Circuits (maximum) | 1 |
| Color - Resin | Blue |
| Gender | N/A |
| Material - Plating Mating | Tin |
| Material - Resin | PVC |
| Net Weight | 7.970/g |
| Number of Rows | 1 |

| | |
|---|---|
| Packaging Type | Bag |
| Single Ended | Yes |
| Stud Size | 10 (M5) |
| Wire/Cable Type | UL 1015 |
| Wire Size (AWG) | 16 |