



Color: ■ dark gray



Electrical data

Ratings per IEC/EN	
Nominal voltage (III/3)	400 V
Rated current	41 A

Physical data

Width	12.3 mm / 0.484 inches
Height	10.74 mm / 0.423 inches
Depth	23.9 mm / 0.941 inches
Jumper assignment	1-2



Mechanical data		
Use	with locking	

Material data		
Note (material data)	Information on material specifications can be found here	
Color	dark gray	
Insulation material (main housing)	Polyamide (PA66)	
Fire load	0 MJ	
Weight of insulation material	0.45 g	
Weight	2.9 g	

Environmental requirements		
Continuous operating temperature	-60 ... +105 °C	

Commercial data		
ETIM 9.0	EC000489	
ETIM 8.0	EC000489	
PU (SPU)	5 pcs	
Packaging type	Bag	
Country of origin	CN	
GTIN	4055144067873	
Customs tariff number	85366990990	

Environmental Product Compliance		
RoHS Compliance Status	Compliant,No Exemption	

Downloads		
Environmental Product Compliance		
Compliance Search		
Environmental Product Compliance 221-941		

Documentation			
Bid Text			
221-941	xml	2.95 KB	
221-941	docx	27.49 KB	

CAD/CAE-Data


CAD data

2D/3D Models 221-941




Installation Notes

Commoning



Extending the N and PE (ground) distribution via jumper

Commoning




Insert the jumper without a locking function into open clamping units.

Commoning




Without a locking function:
The jumper without a locking function is plugged into the splicing connectors.

Commoning



Remove the locking mechanism for intentional jumper removal.



Remove the jumper from open clamping units.