







Leiterplatten-Layout Vorschlag / PCB-layout proposal




1.) Durchmesser des Bohrers / Drill tool




Einzelheit X / detail X
M 20:1 / scale 20:1

Verpackt im Gurt in Anlehnung an DIN IEC 60286-3
tape on reel packaging according to DIN IEC 60286-3
Verpackungseinheit: 240 Stück
packaging unit: 240 pcs



Abspulrichtung - Reel off Direction




Anforderungsstufe 1
Performance Level 1

Kontaktbereich vergoldet
Mating Area gold plating

Anschlussbereich verzinnt 4-6 µm
Terminal Area 4-6 µm tin plating

Koplanarität der Anschlüsse ≤ 0,1 mm
Coplanarity Area of Termination ≤ 0,1 mm

Information:		Tolerances	 All Dimensions in mm	Scale	5:1
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Subject to modification without prior notice. Drawing will not be updated.		Designation	
				Federleiste 10mm SMD, 50 polig Female 10mm SMD, 50 contacts	
g	20.10.2017	 www.ERNI.com		224516	
Index	Date			I A3	
				Class	MSPEED

Copyright by ERNI GmbH
Proprietary notice pursuant to ISO 16016 to be observed.