




**Part Number :** [2249330004](#)  
**Product Description :** 15.00mm Pitch Lever  
Activated Fixed Mount PCB Terminal Block, 35° Wire  
Entry, Bussed Terminals, 4 Circuits  
**Series Number :** 224933  
**Status :** Active  
**Product Category :** Terminal Blocks and Barrier  
Strip  
**Engineering Number :** MX-TLM-705A-15-04



## Documents & Resources

### Drawings

[2249330004\\_sd.pdf](#)

### 3D Models and Design Files

[STEP AP242](#)

[SOLIDWORKS](#)

[Creo](#)

### Specifications

[1302270418-000.pdf](#)

## Product Environment Compliance

### Compliance

|                    |                                                                                                              |
|--------------------|--------------------------------------------------------------------------------------------------------------|
| GADSL/IMDS         | Not Relevant                                                                                                 |
| China RoHS         | <br>per SJ/T 11365-2006 |
| EU ELV             | Not Relevant                                                                                                 |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                                                                               |
| REACH SVHC         | Not Contained per D(2024)7663-DC<br>(21 Jan 2025)                                                            |
| EU RoHS            | Compliant per EU 2015/863                                                                                    |

### Compliance Statements

- EU RoHS
- REACH SVHC

- Low-Halogen

#### Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

#### Substances of Interest

- PFAS

#### EU RoHS Certificate of Compliance

#### Additional Product Compliance Information

---

## Part Details

### General

|                |                                                                                                            |
|----------------|------------------------------------------------------------------------------------------------------------|
| Status         | Active                                                                                                     |
| Category       | Terminal Blocks and Barrier Strip                                                                          |
| Series         | 224933                                                                                                     |
| Description    | 15.00mm Pitch Lever Activated Fixed Mount PCB Terminal Block, 35° Wire Entry, Bussed Terminals, 4 Circuits |
| Application    | Wire-to-Board                                                                                              |
| Component Type | One Piece                                                                                                  |
| Product Name   | Lever Activated Fixed Mount                                                                                |
| Type           | PCB Terminal Blocks and Connectors                                                                         |
| UPC            | 196823649493                                                                                               |

### Electrical

|                               |       |
|-------------------------------|-------|
| Current - Maximum per Contact | 72.0A |
| Voltage - Maximum             | 300V  |

### Physical

|                    |           |
|--------------------|-----------|
| Circuits (Loaded)  | 4         |
| Circuits (maximum) | 4         |
| Color - Resin      | Green     |
| Entry Angle        | 35° Angle |

|                                |                             |
|--------------------------------|-----------------------------|
| Lock to Mating Part            | None                        |
| Material - Metal               | Copper Alloy                |
| Material - Plating Mating      | Tin                         |
| Material - Plating Termination | Tin                         |
| Material - Resin               | Polyamide                   |
| Net Weight                     | 3.900/kg                    |
| Number of Rows                 | 1                           |
| Orientation                    | Vertical                    |
| Panel Mount                    | No                          |
| PCB Thickness - Recommended    | 2.00mm                      |
| PC Tail Length                 | 3.60mm                      |
| Pitch - Mating Interface       | 15.00mm                     |
| Pitch - Termination Interface  | 15.00mm                     |
| Polarized to Mating Part       | N/A                         |
| Stackable                      | No                          |
| Temperature Range - Operating  | -40° to +115°C              |
| Termination Interface Style    | Through Hole                |
| Wire Size (AWG)                | 4, 6, 8, 10, 12, 14, 16, 18 |
| Wire Size mm <sup>2</sup>      | 1.24-5.89                   |