2341474-2 ✔ ACTIVE

LUMAWISE | LUMAWISE Endurance S

TE Internal #: 2341474-2

Accessory, Light Gray, 15.5 mm Height, Keyed / Not Vented, Zhaga, Sealable, -40 – 90 °C [-40 – 194 °F], LUMAWISE Endurance S

View on TE.com >

Connectors > Lighting Connectors > Street Lighting Controls > Street Lighting Connectors







Lighting Product Type: **Accessory**

Primary Product Color: **Light Gray**

Product Height: **15.5 mm**

Lighting Connector Features Included: **Keyed, Not Vented**

Compatible With Agency/Standards Products: **Zhaga**

Features

Product Type Features

Lighting Product Type	Accessory
Sealable	Yes

Configuration Features

Lighting Connector Features Included	Keyed, Not Vented

Body Features

Primary Product Color	Light Gray

Dimensions

Product Diameter	43.5 mm
Product Height	15.5 mm

Usage Conditions

Operating Temperature Range	-40 – 90 °C[-40 – 194 °F]

Industry Standards

Compatible With Agency/Standards Products	Zhaga

Product Compliance


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts




TE Part # 1-2363638-2
Rcpt,LUMAWISE Endurance S2 Kit, KeyA,Dots

TE Part # 2-2343403-1
RECEPTACLE, LUMAWISE ENDURANCE S, KEYED



TE Part # 2343403-1
RECEPTACLE, LUMAWISE ENDURANCE S, KEYED



TE Part # 2363638-2
Recept, LUMAWISE Endurance S2 Kit, KeyA



TE Part # 2363638-6
Recept, LUMAWISE Endurance S2,Key A




TE Part # 1-2363638-6
Rcpt, LUMAWISE Endurance S2,Key A, Dots



TE Part # 2505632-4
LITE BRKT ASM BASIC, LUMA END. S, KEYED



TE Part # 2382635-1
LUMAWISE POWER INPUT TERMINAL BLOCK (TB)



TE Part # 2505632-3
LITE BRACKET ASM, LUMAWISE END. S. KEYED




TE Part # 1-2343403-1
RECEPT ASSY, LUMAWISE ENDURO S, KEYED



TE Part # 2452802-2
LUMAWISE ENDURANCE S Recept, 33mm, Key A

Also in the Series | LUMAWISE Endurance S



Poke-In Connectors(1)



Street Lighting Connectors(47)



Street Lighting Power Management(5)

Customers Also Bought




TE Part #T4113012051-000
M12 M, 5P GOLD A_CODE RA SHIELDED PG9



TE Part #1SNK512010R0000
ZS25




TE Part #8-1879512-6
CRGH0805 1% 12R 0.33W



TE Part #1879643-4
H8 500R 0.25% 50PPM




TE Part #4-1879694-1
H8 3K01 0.1% 100PPM



TE Part #2176244-5
CRGS0805 5% 2R2



TE Part #2213831-3
BASE ASSY, 80MM, SEALED



TE Part #2311664-1
COVER, 76MM DIAMETER, 75MM HEIGHT



TE Part #1-2329013-1
LUMAWISE 40MM DIA DOME CLEAR LOW



TE Part #2343403-1
RECEPTACLE, LUMAWISE ENDURANCE S, KEYED

Documents

Product Drawings

SEALING CAP, RCPT, LUMAWISE ENDURANCE S

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2341474-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2341474-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2341474-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages

Datasheet - Lumawise Z10

English

Lumawise Endurance S Modules

English

Product Specifications

Application Specification

English

Agency Approvals

CB_CERT_IEC_61984_US_34131_M1_UL_C1

English

UL_EU_CERT_EN_61984_UL_EU_01778_M1_C1

English

CB_CERT_US_34131_M1_UL_4788988643_TR_C1

English