

# C-ME 6/1 - Operating lever

3034441

<https://www.phoenixcontact.com/nl/products/3034441>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Operating lever, for switching test disconnect terminal blocks on and off

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 3034441       |
| Packing unit                         | 10 pc         |
| Minimum order quantity               | 10 pc         |
| Sales key                            | BE2ZWX        |
| Product key                          | BE2ZWX        |
| GTIN                                 | 4046356959292 |
| Weight per piece (including packing) | 0,65 g        |
| Weight per piece (excluding packing) | 0,62 g        |
| Customs tariff number                | 39269097      |
| Country of origin                    | PL            |

# C-ME 6/1 - Operating lever

3034441

<https://www.phoenixcontact.com/nl/products/3034441>



## Technical data

### Product properties

|                     |   |
|---------------------|---|
| Number of positions | 1 |
|---------------------|---|

### Dimensions

|        |         |
|--------|---------|
| Width  | 8.1 mm  |
| Height | 7.7 mm  |
| Depth  | 23.1 mm |

### Material specifications

|                                        |                   |
|----------------------------------------|-------------------|
| Color                                  | orange (RAL 2003) |
| Material                               | PA                |
| Flammability rating according to UL 94 | V0                |

### Environmental and real-life conditions

#### Ambient conditions

|                                          |                                                                           |
|------------------------------------------|---------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 85 °C                                                          |
| Ambient temperature (storage/transport)  | -25 °C ... 55 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                           |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                           |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                             |

# C-ME 6/1 - Operating lever

3034441

<https://www.phoenixcontact.com/nl/products/3034441>



## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27250392 |
| ECLASS-15.0 | 27250392 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC002848 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# C-ME 6/1 - Operating lever

3034441

<https://www.phoenixcontact.com/nl/products/3034441>



## Environmental product compliance

### EU RoHS

|                                         |                    |
|-----------------------------------------|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|-----------------------------------------|--------------------|

### China RoHS

|                                        |                                          |
|----------------------------------------|------------------------------------------|
| Environment friendly use period (EFUP) | EFUP-E                                   |
|                                        | No hazardous substances above the limits |

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

### EF3.1 Climate Change

|         |               |
|---------|---------------|
| CO2e kg | 0,002 kg CO2e |
|---------|---------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT B.V.  
Hengelder 56 6902 PA Zevenaar  
Postbus 246 6900 AE Zevenaar  
(0316) 59 17 20  
[sales@phoenixcontact.nl](mailto:sales@phoenixcontact.nl)