



Part Number : [330001001](#)
Product Description : MX150 Male Terminal for
Mat-Sealed or Unsealed Connectors, Tin Plating, 14
AWG, Left Reel Payoff
Series Number : 33000
Status : Active
Product Category : Crimp Terminals



Documents & Resources

Drawings

[330001001_sd.pdf](#)
[313025040-000.pdf](#)

Specifications

[AS-33000-001-001.pdf](#)
[AS-33000-001-FR-001.pdf](#)
[AS-33000-001-001.pdf](#)
[PS-33012-002-001.pdf](#)
[TS-33000-001-001.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant with Exemption 34; 33
China RoHS	 per SJ/T 11365-2006
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2025)4165-DC (25 June 2025)
EU RoHS	Compliant per EU 2015/863

Compliance Statements

- EU RoHS
- REACH SVHC

- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

Part Details

General

Status	Active
Category	Crimp Terminals
Series	33000
Description	MX150 Male Terminal for Mat-Sealed or Unsealed Connectors, Tin Plating, 14 AWG, Left Reel Payoff
Application	Power, Wire-to-Board, Wire-to-Wire, Automotive
Comments	Left Reel Payoff
Product Name	MX150
UPC	756054586280

Electrical

Current - Maximum per Contact	Contact Molex
Voltage - Maximum	14V DC

Physical

Durability (mating cycles max)	25
Gender	Male
Grip Code	14
Material - Metal	High Performance Alloy (HPA)
Material - Plating Mating	Tin
Material - Plating Termination	Tin

Net Weight	0.481/g
Packaging Type	Reel
Plating min - Mating	0.508µm
Plating min - Termination	0.508µm
Termination Interface Style	Crimp or Compression
Wire Insulation Diameter	2.70mm max.
Wire Size (AWG)	14
Wire Size mm ²	1.50

Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----

Mates With / Use With

Use with Part(s)

Description	Part Number
MX150 Mat-Sealed Single Row Male Connector Assemblies	<u>33481</u>
MX150 Mat-Sealed Dual Row Male Connector Assemblies	<u>33482</u>

Application Tooling

Global

Description	Part Number
Extraction Toolkit for MX150 Connectors	<u>2002220700</u>
FA2 Mechanical Feed Crimp Applicator for MX150 Crimp Terminals, 14 AWG, 1.50mm ² and 2.00mm ² Wire	<u>638087900</u>
FA2 Pneumatic Feed Crimp Applicator for MX150 Crimp Terminals, 14 AWG, 1.50mm ² and 2.00mm ² Wire	<u>638087910</u>
PremiumGrade Hand Crimp Tool for 1.50mm MX150 Blade Male	<u>638112400</u>

Terminals, 16-14 AWG	
Extraction Tool for MX150L, MX150, PT Bulb Socket, iGrid, SPOX, and Wire-to-Motor Terminals	<u>638131500</u>
FineAdjust Applicator for SRC Connector using MX150 (M3) Blade Terminals, 1.50mm ² wires	<u>639041000</u>
FineAdjust Applicator for SRC Connector using MX150 (M3) Blade Terminals, 2.00mm ² wires	<u>639041100</u>