**Part Number :** 350220015
**Product Description :** 2.50mm Pitch, Board-In Crimp Housing, Right-Angle and Vertical, 15 Circuits, Natural
**Series Number :** 35022
**Status :** Active
**Product Category :** Connector Housings



## Documents & Resources

### Drawings

350220015_sd.pdf

### 3D Models and Design Files

STEP AP242

SOLIDWORKS

Creo

### Specifications

PK-35022-001-001.pdf

PS-35021-001-001.pdf

PS-35022-003-001.pdf

## Product Environment Compliance

### Compliance

| | |
|---|---|
| GADSL/IMDS | Not Relevant |
| China RoHS | per SJ/T 11365-2006 |
| EU ELV | Compliant per 2000/53/EC |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2025)4165-DC (25 June 2025) |
| EU RoHS | Compliant per EU 2015/863 |

Compliance Statements

- EU RoHS

- REACH SVHC
- Low-Halogen

Industry Documents
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest
- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

---

## Part Details

### General

| | |
|---|---|
| Status | Active |
| Category | Connector Housings |
| Series | 35022 |
| Description | 2.50mm Pitch, Board-In Crimp Housing, Right-Angle and Vertical, 15 Circuits, Natural |
| Application | Signal |
| Product Name | Board-in |
| UPC | 800753576971 |

### Agency

| | |
|---|---|
| CSA | LR19980 |
| UL | E29179 |

### Physical

| | |
|---|---|
| Circuits (maximum) | 15 |
| Color - Resin | Natural |
| Flammability | 94V-0 |
| Gender | N/A |
| Glow-Wire Capable | No |
| Lock to Mating Part | None |
| Material - Resin | Nylon |

| | |
|---|---|
| Net Weight | 0.380/g |
| Number of Rows | 1 |
| Packaging Type | Bag |
| Panel Mount | No |
| Pitch - Mating Interface | 2.50mm |
| Stackable | No |
| Temperature Range - Operating | -40° to +105°C |

**Solder Process Data**

| | |
|---|---|
| Lead-Free Process Capability | N/A |

## Mates With / Use With

**Use with Part(s)**

| Description | Part Number |
|---|---|
| 2.50mm Pitch, Board-in Male Crimp Terminal, Right-Angle, Brass Tin (Sn) Plating, 28-22 AWG, Reel | 350211001 |
| 2.50mm Pitch, Board-in Male Crimp Terminal, Right-Angle, Tin (Sn) Plating, 28-22 AWG, Reel | 350211160 |