



Terminals & Splices > Ring Terminals



Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 33100 – 52600 CMA

Stud Size: 5/8, M16

Features

Product Type Features

Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	5/8, M16
Sealable	No

Wire Insulation Support Retention Type	Non-Insulation Support
--	------------------------

Configuration Features

Number of Holes	1
-----------------	---

Body Features

Product Weight	17.199 g
----------------	----------

Contact Features

Barrel Type	Closed
Terminal Orientation	Straight
Terminal Plating Material	Tin

Mechanical Attachment

Wire Insulation Support	Without
-------------------------	---------

Dimensions

Wire Size	33100 – 52600 CMA
Stud Diameter	16.66 mm[.656 in]
Tongue Thickness	1.78 mm[.07 in]
Product Length	53.09 mm[2.09 in]
Barrel Inside Diameter	7.57 mm[.298 in]

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	0 – 170 °C[0 – 338 °F]

Operation/Application

Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin

Industry Standards

Government Qualified Terminal	No
-------------------------------	----

Packaging Features

Packaging Quantity	100
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these




limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 48129
HYP8 SOLIS 4AWG NEST



TE Part # 1901000-2
NEST #4



TE Part # 69218
HYP8/10 SOLIS 4AWG DIE SET



TE Part # 1490414-2
HYP10 SOLIS HD 6-4AWG INDENTER




TE Part # 1490413-3
HYP10 SOLIS 4AWG NEST



TE Part # 48127
HYP8 SOLIS 6-2AWG INDENTER

Customers Also Bought



TE Part #1SNG607008R0000
EP-LN-M20-GR-A



TE Part #TRAB8903NP
OMNI,SB,Ph,890-960MHz 3,NGP PMT



TE Part #36809
TERMINAL,SOLIS R 6 5/8



TE Part #52350
TERMINAL R PG 6 1/2



TE Part #322224
TERMINAL,SOLIS R 2/0 5/8




TE Part #710030-7
XCT 16-10



TE Part #710031-8
XCT 10-10



TE Part #710036-4
XCT 35-12



Documents

Product Drawings

TERMINAL,SOLIS R 4 5/8

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_35669_P.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_35669_P.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_35669_P.3d_stp.zip

English

Customer View Model

ENG_CVM_35669_D1.3d_igs.zip

English

Customer View Model

ENG_CVM_35669_D1.3d_stp.zip

English

Customer View Model

ENG_CVM_35669_D1.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

UL Report

English

35669

Closed Ring Tongue Terminal, 4 AWG, 5/8 / M16 Stud, 16.66 mm [.656 in] Stud Diameter, Closed Barrel, Straight, Tin Plating, Uninsulated



UL Report

English