



Junior Power Timer

TE Internal #: 368162-1
12 V, 4 Position, Automotive Housing for Female Terminals, Wire-to-Wire, 5 mm [.197 in] Centerline, Sealable, Black, Wire & Cable, Junior Power Timer

[View on TE.com >](#)

Automotive Parts > Automotive Connectors > Automotive Housings > Timer Connector Housing



Nominal Voltage Architecture: 12 V
Connector & Housing Type: **Housing for Female Terminals**
Number of Positions: 4
Sealable: **Yes**
Operating Temperature Range: -40 – 130 °C [-40 – 266 °F]

[All Timer Connector Housing \(436\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Primary Locking Feature	Locking Lance
Connector System	Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	4
Number of Rows	1

Electrical Characteristics

Operating Voltage	12 VDC
-------------------	--------



Nominal Voltage Architecture	12 V
------------------------------	------

Body Features

Cable Exit Angle	180 °
Primary Product Color	Black

Contact Features

Contact Size	2.8mm
Contact Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Contact Current Rating (Max)	30 A

Mechanical Attachment

Strain Relief	Without
Terminal Position Assurance	No
Mating Alignment Type	Polarizing Rib
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PA 66 GF15
Centerline (Pitch)	5 mm[.197 in]

Dimensions

Product Width	30.5 mm[1.2 in]
Product Length	29.3 mm[1.15 in]
Connector Height	12.3 mm[.48 in]

Usage Conditions

Operating Temperature Range	-40 – 130 °C[-40 – 266 °F]
Operating Temperature (Max)	130 °C[266 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Packaging Features

Packaging Quantity	250
Packaging Method	Bag

Other

--	--



Serviceable	No
Connector Position Assurance Capable	No

Product Compliance


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 368130-1
JPT 4P FOR MAP SENSOR CONN HSG



TE Part # 368840-1
RUBBER SEAL-MAP SENSOR 4P ORAN



TE Part # 2219574-2
COVER HSG FOR JPT 4P




TE Part # 2005484-2
JPT 4P COVER HSG FOR XM



TE Part # CAT-T4827-T273
TIMER, RECEPTACLE AND TAB

Also in the Series | Junior Power Timer



Automotive Connector Locks & Position Assurance(8)




Automotive Housings(279)



Automotive Seals & Cavity Plugs(8)



Automotive Signal & Power Connector Housings(275)



Module Components(1)




Other Automotive Connector Accessories(3)

Customers Also Bought



TE Part #936060-2
2.8MM SLD 3P PLUG ASSY-TDC



TE Part #1743089-2
LIF HYB 39P PLUG ASSY BLK




TE Part #2289990-1
BLIND PLUG,DIRECT CONNECTOR




TE Part #2305186-1
44POS,PR SPRNG CONTACT,REC HSG ASSY,SL



TE Part #2373835-1
2POS,MQS,REC HSG ASSY,SLD,COD A



TE Part #2066043-2
12 POS. ECONOSEAL CAP HOUSING JMARK II+



TE Part #2312552-1
COVER,44P DIRECT CONNECTOR



TE Part #2378907-1
46POS,HYBRID,REC HSG ASSY,SLD, COD A



Documents

Product Drawings

JPT 4P ASSY FOR MAP SENSOR ORA

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_368162-1_D.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_368162-1_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_368162-1_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English